



Telecommunications
Standards Advisory
Committee (TSAC)

2nd Generation Digital
Terrestrial Television
Broadcasting System
(DVB-T2)

Technical
Specification

Integrated Receiver
Decoder (IRD)

**Draft IMDA TS DVB-T2 IRD
Issue 1 Revision 1, September 2017**

Info-communications Media Development Authority
Resource Management & Standards
10 Pasir Panjang Road
#10-01 Mapletree Business City
Singapore 117438

© Copyright of IMDA, 2017

This document may be downloaded from the IMDA website at <http://www.imda.gov.sg> and shall not be distributed without written permission from IMDA.

Acknowledgement

The Info-communications Media Development Authority (IMDA) and the Telecommunications Standards Advisory Committee (TSAC) would like to acknowledge the following members of the TSAC Working Group 3 Digital Terrestrial Television Broadcasting System (DVB-T2) Task Force (TSAC WG3 DVB-T2 TF) for their invaluable contributions to the preparation of this Technical Specification.

IMDA TS DVB-T2 IRD Issue 1 Revision 1, September 2017	Technical Specification for Integrated Receiver Decoder for use with second generation Digital Terrestrial Television broadcasting system (DVB-T2)
TSAC WG3 Chairman	Dr Tham Jo Yew, Institute for Infocomm Research, Agency for Science, Technology and Research
TSAC WG3 Co-Chairman	Assoc Prof Steven Wong, Singapore Institute of Technology
TSAC WG3 DVB-T2 TF Chairman	Mr Tan Jek Thoon, MediaCorp Pte Ltd
TSAC WG3 DVB-T2 TF Editor(s) TSAC WG3 DVB-T2 TF Secretary	Ms Agnes Chong, Info-communications Media Development Authority

List of TSAC WG3 DVB-T2 TF Members

S/N	Organisation	Name
1	Info-communications Media Development Authority	Mr Lim Chin Siang
2	Info-communications Media Development Authority	Ms Tan Sze Siang
3	Info-communications Media Development Authority	Mr Calvin Lim
4	LG Electronics Singapore Pte Ltd	Mr Brian Yi
5	LG Electronics Singapore Pte Ltd	Ms Sharon Jieling Soon
6	MediaCorp Pte Ltd	Mr Goh Kim Soon
7	MediaCorp Pte Ltd	Mr Peh Beng Yeow
8	MediaCorp Pte Ltd	Mr Yeo Kim Pow
9	MediaCorp Pte Ltd	Mr Lau Hing Ting
10	MediaCorp Pte Ltd	Mr Roland Tan
11	Panasonic Singapore R&D Pte Ltd	Mr Philip Ong
12	Panasonic Singapore R&D Pte Ltd	Mr Tan Li Jia
13	Samsung Asia Pte Ltd	Mr Gavin Yeong
14	Samsung Asia Pte Ltd	Mr Foo Yong Yee
15	Samsung Electronics Co Ltd	Mr Chun Youngshin
16	Samsung Electronics Co Ltd	Mr Kim Kee Hyun
17	Samsung Asia Pte Ltd	Mr Sun Giong Ko
18	Sharp Roxy Sales (Singapore) Pte Ltd	Mr Dennis Quek Kwang Meng
19	Sharp Roxy Sales (Singapore) Pte Ltd	Mr Ngiam Tee Wei
20	Skycom Satellite Systems Pte Ltd	Mr Simon Tso
21	Skycom Satellite Systems Pte Ltd	Mr William Tay
22	Skycom Satellite Systems Pte Ltd	Mr Ben Iral
23	Sony EMCS (Malaysia) Sdn. Bhd.	Mr Muzaffar Fakhruddin
24	Sony EMCS (Malaysia) Sdn. Bhd.	Mr Stephen Cleary
25	Sony Electronics (Singapore) Pte Ltd	Ms Lin Jiahui
26	Sony Electronics (Singapore) Pte Ltd	Mr Shawn Tan
27	Sony Electronics (Singapore) Pte Ltd	Mr Ong Hock Seng
28	Sony Electronics (Singapore) Pte Ltd	Mr Ngiam Lee Ni
29	Sony Electronics (Singapore) Pte Ltd	Mr Joshua Quek
30	Sony Electronics (Singapore) Pte Ltd	Mr Eden Cheok
31	StarHub Ltd	Ms Ong Bee Lian
32	StarHub Ltd	Mr Lu Jin
33	Toshiba Singapore Pte Ltd	Mr Adrian Fang
34	Toshiba Singapore Pte Ltd	Mr Ronald So

S/N	Organisation	Name
35	TP Vision Singapore Pte Ltd	Mr Gwee Teow How
36	TP Vision Singapore Pte Ltd	Mr Leonard Shee
37	TP Vision Singapore Pte Ltd	Mr Low Kwong Wai

Assoc Prof Ian Thng Li-Jin	Programme Director Singapore Institute of Technology
Dr Wong Woon Kwong	Director, Research and Industry Collaborations Singapore University of Technology and Design
Mr Kuan Wai Mun	Associate Director, Radio Network Quality Singapore Telecommunications Ltd
Mr Lew Yoon Heng	Senior Engineering Manager Singapore Telecommunications Ltd
Mr Adrian Goh	Deputy Director, Standards SPRING Singapore
Mr Lim Eng Huat	Vice President Starhub Ltd
Mr Hong Tse Min	Assistant Director, Resource Management and Standards Info-communications Media Development Authority
Ms Woo Yim Leng	Senior Manager, Resource Management and Standards Info-communications Media Development Authority

This page is intentionally left blank.

Content

Section	Title	Page
	Introduction	2
Part A	Basic DVB-T2 IRD Requirements	3
1.	Scope	3
2.	References	3
3.	Abbreviations	5
4.	General Requirements	6
5.	Use of Video and Audio Coding in Broadcasting Applications based on the MPEG-2 Transport Stream	8
6.	Frontend Characteristics	12
7.	Service Information (SI)	14
8.	Services	18
9.	Interfaces and Connectors	21
10.	Firmware Operation	23
Part B	Additional DVB-T2 IRD Requirements for supporting Multi-channel Audio	25
Part C	Exceptions for other DVB-T2 IRD Implementations	27
Annex A	AFD Illustration for Required TV Output Display	28
Annex B	Broadcast Channel Numbers and Centre Frequencies	29
Annex C	Classification Code Matrix	30
Annex D	Basic and Digital TV Function Keys	31
Annex E	DVB-T2 Performance Requirements	32
Annex F	Proposed Logical Channel Numbering (LCN) Range	34
Annex G	List of Broadcast Descriptors	35
Annex H	Addendum/Corrigendum	36
	Changes to IMDA TS DVB-T2 IRD, Issue 1, Dec 2016	
	Changes to IDA/MDA TS DVB-T2 IRD, Issue 1, Rev 2, May 14	
	Changes to IDA/MDA TS DVB-T2 IRD, Issue 1, Rev 1, Mar 13	
	Changes to IDA/MDA TS DVB-T2 IRD, Issue 1, Nov 12	

NOTICE

THE INFO-COMMUNICATIONS MEDIA DEVELOPMENT AUTHORITY (“IMDA”) MAKES NO WARRANTY OF ANY KIND WITH REGARD TO THE MATERIAL PROVIDED HEREIN AND EXCLUDE ANY EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS OF NON-INFRINGEMENT, MERCHANTABILITY, SATISFACTORY QUALITY AND FITNESS FOR A PARTICULAR PURPOSE. SUBJECT TO THE MAXIMUM EXTENT PERMITTED UNDER LAW, IMDA SHALL NOT BE LIABLE FOR ANY ERRORS AND/OR OMISSIONS CONTAINED HEREIN OR FOR ANY LOSSES OR DAMAGES (INCLUDING ANY LOSS OF PROFITS, BUSINESS, GOODWILL OR REPUTATION, AND/OR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES) IN CONNECTION WITH THE USE OF THIS MATERIAL.

IMDA DRAW ATTENTION TO THE POSSIBILITY THAT THE PRACTICE OR IMPLEMENTATION OF THIS STANDARD/SPECIFICATION MAY INVOLVE THE USE OF INTELLECTUAL PROPERTY RIGHTS AND TAKE NO POSITION CONCERNING THE EXISTENCE, VALIDITY AND/OR APPLICABILITY OF ANY SUCH INTELLECTUAL PROPERTY RIGHTS, WHETHER ASSERTED BY TSAC MEMBERS OR ANY THIRD PARTY.

AS OF THE DATE OF APPROVAL OF THIS STANDARD, IMDA HAVE RECEIVED WRITTEN NOTICE ON PATENT RIGHTS WHICH MAY BE RELEVANT IN RELATION TO THE IMPLEMENTATION OF THIS STANDARD/SPECIFICATION. FOR EXAMPLE, PLEASE NOTE THAT ITEMS RELATING TO VIDEO / AUDIO CODEC, INCLUDING BUT NOT LIMITED TO MPEG, H.264 AND E-AC3 MAY SUBJECT TO PATENT LICENSING. HOWEVER, IMPLEMENTERS ARE CAUTIONED THAT THIS MAY NOT REPRESENT THE LATEST INFORMATION AND ARE THEREFORE STRONGLY URGED TO CHECK WITH THE RELEVANT DATABASE IN ITU, ISO, IEC OR THE RELATED STANDARDS DEVELOPMENT ORGANISATION FOR INFORMATION OF PATENT RIGHTS. IMPLEMENTERS ARE ADVISED TO OBTAIN THEIR OWN LEGAL AND/OR TECHNICAL ADVICE IN RELATION TO THE IMPLEMENTATION OF THE STANDARD/SPECIFICATION IF REQUIRED.

Integrated Receiver Decoder (IRD) for use with the second generation Digital Terrestrial Television Broadcasting System (DVB-T2)

Introduction

1. This Specification defines the requirements for the Integrated Receiver Decoder (IRD) functionality which may be incorporated as a standalone module such as a Set-Top Box (STB), an Integrated Digital Television (IDTV) or any other similar device intended for use with the second generation Digital Terrestrial Television broadcasting system (DVB-T2). The requirements for advanced features such as Personal Video Recorders (PVRs) and interactive services are not included in the scope of this Specification.
2. This Specification is established to enable equipment manufacturers and/or suppliers to bring in DVB-T2 IRD modules and IDTVs that will provide good indoor reception of Free-To-Air (FTA) Digital Terrestrial Television (DTT) services. For the purpose of this Specification, the IRD functioning as standalone modules or built-in modules of IDTVs shall be termed "DVB-T2 IRD".
3. This Specification comprises 3 parts: Part A on "Basic DVB-T2 IRD Requirements", which specifies the minimum requirements for using the DVB-T2 IRD with DTT networks; Part B on "Additional DVB-T2 IRD Requirements for supporting Multi-channel Audio" is to be applied in addition to Part A for DVB-T2 IRDs that are capable of supporting the multi-channel audio feature defined therein; Part C sets out the exceptions to the Part A requirements to which other DVB-T2 IRD implementations, such as PC cards, dongles, portable TV or similar devices, may not need to comply.

Part A Basic DVB-T2 IRD Requirements

1 Scope

- 1.1 Part A of this Specification (§ 4) defines the minimum requirements for the DVB-T2 IRD in accordance with the implementation guidelines outlined in the DVB Specification for the use of video and audio coding in broadcasting applications based on the MPEG-2 transport stream (ETSI TS 101 154 [1]). The minimum functionality of the DVB-T2 IRD shall be defined by the following dimensions:
- a) 25 Hz and 50 Hz;
 - b) SDTV and HDTV;
 - c) Input and Output interfaces;
 - d) MPEG-2 and H.264/AVC video coding formats¹; and
 - e) MPEG-1 Layer II and MPEG-4 HE-AAC audio coding formats².
- 1.2 Part A of this Specification (§ 5) requires that the DVB-T2 IRD be compatible with the DVB-T2 baseline system for DTT as defined in the ETSI EN 302 755 [2] as well as the DVB-T baseline system as defined in the ETSI EN 300 744 [3].
- 1.3 Part A of this Specification also requires that the DVB-T2 IRD be capable of decoding Singapore's FTA DVB-T and DVB-T2 broadcast of television, radio and enhanced services (§ 6 and § 7). This shall include the following capabilities:
- a) Subtitling (where available and selected by viewer);
 - b) Audio Description
 - c) Electronic Program Guide;
 - d) Teletext (Optional);
 - e) Parental Lock Feature; and
 - f) Multiple Audio Selection

Note: Unless otherwise specified, all requirements are mandatory.

The word "Recommended" means this item is not mandatory but is highly recommended.

2 References

For the technical requirements captured in this Specification, reference has been made to the following standards. Where versions are not indicated, implementation of this Specification shall be based on current and valid versions of these standards published by the respective Standards Development Organisations.

- [1] ETSI TS 101 154 v.1.11.1 (2012-11) Digital Video Broadcasting (DVB); Specification for the use of Video and Audio Coding in Broadcasting Applications based on the MPEG-2 Transport Stream
- [2] ETSI EN 302 755 v1.3.1 (2012-04) Frame structure channel coding and modulation for a

¹ Please note that such coding formats may be intellectual property of third parties.

² Same as Footnote 1.

- second generation digital terrestrial television broadcasting system (DVB-T2)
- [3] ETSI EN 300 744 v1.6.1 (2009-01) Digital Video Broadcasting (DVB); Framing structure, channel coding and modulation for digital terrestrial television
 - [4] IEC 60065: Audio, video and similar electronic apparatus – Safety requirements
 - [5] IEC 62368-1: Audio/video, information and communication technology equipment – Part 1: Safety requirements
 - [6] IEC CISPR 32: Electromagnetic compatibility of multimedia equipment – Emission requirements
 - [7] IEC CISPR 20: Sound and television broadcast receivers and associated equipment – Immunity characteristics – Limits and methods of measurement
 - [7a] IEC 61000-4-3 (2010-04): Testing and measurement techniques – Radiated, radio-frequency, electromagnetic field immunity test
 - [8] ITU-T K.74 (2015): Electromagnetic compatibility, resistibility and safety requirements for home network devices
 - [9] ITU-T K.116 (2015): EMC requirements and test methods for radio telecommunication terminal equipment
 - [10] ITU-T Rec. H.222.0 / ISO/IEC 13818-1 (2012), Information technology – Generic coding of moving pictures and associated audio information: Systems
 - [11] ITU-T Rec. H.262 / ISO/IEC 13818-2 (2012), Information technology – Generic coding of moving pictures and associated audio information: Video
 - [12] ITU-T Rec. H.264 / ISO/IEC 14496-10 (01/2012), Infrastructure of audiovisual services – Coding of moving video: Advanced video coding for generic audiovisual services
 - [13] ISO/IEC 13818-3 (Apr 1998) Information technology — Generic coding of moving pictures and associated audio information- Part 3: Audio
 - [14] ISO/IEC 14496-3 (Sep 2009) Information technology — Coding of audio-visual objects — Part 3: Audio
 - [15] ETSI TR 101 211 v1.9.1 (2009-06) Digital Video Broadcasting (DVB) Guidelines on implementation and usage of Service Information (SI)
 - [16] ETSI EN 300 468 v1.13.1 (2012-04) Digital Video Broadcasting (DVB); Specification for Service Information (SI) in DVB systems
 - [17] ISO/IEC 3166-1 Countries and Subdivisions Codes (2006)
 - [18] ISO/IEC 8859 Information technology — 8-bit single-byte coded graphic character sets (1998)
 - [19] ETSI EN 300 743 v1.4.1 (2011-10) Digital Video Broadcasting (DVB); Subtitling systems
 - [20] ETSI EN 300 472 v1.3.1 (2003-05) Digital Video Broadcasting (DVB); Specification for Conveying ITU-R System B Teletext in DVB bitstreams
 - [21] ETSI EN 300 706 v1.2.1 (2003-04) Digital Video Broadcasting (DVB); Enhanced Teletext Specification
 - [22] IEC 61169-2 Radio-frequency connectors – Part 2: Sectional specification – Radio frequency coaxial connectors of type 9,52
 - [23] ITU-R Rec. BT.653-3 (02/1998) Teletext systems
 - [24] ETSI TS 102 006 v1.3.2 (2008-07) Digital Video Broadcasting (DVB); Specification for System Software Update in DVB Systems
 - [25] ETSI TS 102 366 v1.2.1 (2008-8) Digital Audio Compression (AC3, Enhanced AC3) Standard

3 Abbreviations

AC	Alternating Current
ACE	Active Constellation Extension
AC-3	Dolby Digital (5.1 Channel)
AFC	Automatic Frequency Control
ARC	Audio Return Channel
AVC	Advanced Video Coding
BAT	Bouquet Association Table
BER	Bit Error Rate
BPSK	Binary Phase Shift Keying
CVBS	Composite Video Baseband Signal
DC	Direct Current
DIT	Data Information Table
DTS	Digital Theatre System
DVB-T2	Digital Video Broadcasting Terrestrial Second Generation
DVB SI	Digital Video Broadcasting Service Information
E-AC3	Enhanced AC3/ Dolby Digital Plus
EIT	Event Information Table
ETSI	European Telecommunications Standards Institute
FFT	Fast Fourier Transform
FTA	Free To Air
HDCP	High Bandwidth Digital Content Protection
HDMI	High-Definition Multimedia Interface
HE-AAC	High Efficiency Advanced Audio Coding
HEM	High Efficiency Mode
HP	High Profile
LCN	Logical Channel Number
NIT	Network Information Table
MP	Main Profile
MPEG	Moving Pictures Expert Group
OAD	Over Air Download
ONID	Original Network Identification
OTA	Over the Air
OUI	Organization Unique Identifiers
PAT	Program Association Table
PAPR	Peak to Average Power Ratio
PCM	Pulse Code Modulation
PCR	Program Clock Reference
PID	Program Identification Descriptor
PMT	Program Management Table
PP	Pilot Pattern
PLP	Physical Layer Pipe
PSI	Program Specific Information
QAM	Quadrature Amplitude Modulation
QEF	Quasi Error Free
QPSK	Quadrature Phase Shift Keying
RF	Radio Frequency
SDT	Service Description Table
SFN	Single Frequency Network
SI	Service Information
SIT	Selection Information Table
S/PDIF	Sony/Philips Digital Interface
ST	Stuffing Table
TDT	Time and Date Table
TOT	Time Offset Table
RTC	Real Time Clock
UHF	Ultra-High Frequency
VBI	Vertical Blanking Interval
VHF	Very-High Frequency
YPbPr	Component Analogue Output

4 General Requirements

4.1 Power Supply

The DVB-T2 IRD may be AC powered or DC powered. For AC powered DVB-T2 IRD, the Specification shall be complied with when operating from an AC mains supply of voltage, $230V \pm 10\%$ and frequency, $50\text{ Hz} \pm 2\%$ (§1.1.2 of IEC 60065 [4]). For DC powered DVB-T2 IRD, the Specification shall be complied with when drawing power from an external AC/DC converter or from batteries (§4.2.11 of IEC 60065 [4]).

4.2 Electromagnetic Compatibility (EMC) and Safety Requirements

4.2.1 EMC assessment

For the purpose of EMC assessment, the DVB-T2 IRD shall be considered for (a) fixed use (connected to AC mains supply or external AD/DC converter); (b) vehicular use (connected to DC supply of vehicle); or (c) portable use (powered by its integral battery). This will determine the applicability of EMC (emission and immunity) requirements, relating to the input/output ports provided³, as described in §7.1 of ITU-T K.74 [8]. These ports of the DVB-T2 IRD should comply with the relevant EMC requirements defined in IEC CISPR 32 [6] for emission and IEC CISPR 20 [7] for immunity (§7.3 [8]).

4.2.1.1 EMI or emission measurements

- (a) Radiated emissions from the DVB-T2 IRD shall be measured to Class B requirements defined in §4 and Tables A.4 and A.5 of CISPR 32 [6].
- (b) Conducted emissions at the DC power port of the DVB-T2 IRD for fixed use with DC cable longer than 3 m; or for vehicular use irrespective of cable length, shall be measured to Class B requirements defined in §4 and Tables A.10 of CISPR 32 [6]. It shall also be applicable to DC power port that is not powered by dedicated AC/DC power converter (§3.1.12 of [6]).
- (c) Conducted emissions at the AC mains port of the DVB-T2 IRD shall be measured to Class B requirements defined in §4 and Tables A.10 of CISPR 32 [6]. Equipment with a DC power port which is powered by a dedicated AC/DC power converter is defined as AC mains powered equipment (§3.1.1 [6]). Test is also applicable to portable or mobile equipment with dedicated charger/power adapter.
- (d) Conducted emissions at the broadcast receiver tuner port and wired network port of the DVB-T2 IRD (where applicable), shall be measured to Class B requirements defined in §4 and Tables A.12 and/or A.13 of CISPR 32 [6]. Examples of wired network port include CATV and LAN (§3.1.32 [6]).

Note 1: If DVB-T2 IRD is a module intended to be marketed and sold separately from a host, it shall be assessed with at least one representative host system. Modules may be internal, mounted, plug-in or external (§6.2 of CISPR 32 [6]).

Note 2: During emission measurements, the DVB-T2 IRD shall be exercised according to Annex B of CISPR 32 [6], primarily to the test signal specifications of DVB-T2 baseline system outlined §6 of this Specification and defined in EN 302 755 [2]. The DVB-T2 may have several functions and numerous modes of operation associated with each function. The mode(s) that produce the highest emissions shall be selected for final measurements.

³ The input/output ports for home network devices (including DVB-T2 STB or IDTV) may include ports such as AC/DC power ports, input/output ports for access networks, internal connection ports for home network connections, coaxial ports, etc.

4.2.1.2 EMS or immunity testing

The DVB-T2 IRD shall comply with requirements defined in IEC CISPR 20 [7] and IEC 61000-4-3 [7a] for RF electromagnetic field (80 MHz to 1 GHz, 3V/m) immunity testing at the enclosure of the DVB-T2 IRD (IDTV or STB). Performance criteria A with phenomena of a continuous nature shall be applied. There shall be no degradation of performance after the test below the minimum performance level specified by the manufacturer for the intended use of the DVB-T2 IRD (§8 of ITU-T K.116 [9]).

4.2.2 Equipment safety testing

4.2.2.1 The DVB-T2 IRD shall be designed and constructed so that under all normal conditions of use and fault conditions (§4.2 and §4.3 of IEC 60065 [4]), protection is provided against (§3 [4]):

- (a) Hazardous currents passing through the human body (electric shock hazard, §9 and §11.1 [4]);
- (b) Excessive temperatures;
- (c) Hazardous radiations (ionising and laser radiation);
- (d) Effects of implosion and explosion;
- (e) Mechanical instability;
- (f) Injury by mechanical parts; and
- (g) Start and spread of fire.

4.2.2.2 Equipment safety testing or assessment shall be performed on the DVB-T2 IRD to requirements defined in IEC 60065 [4] or IEC 62368-1 [5], based on the following assumptions, where relevant:

- (a) All accessible parts of the DVB-T2 IRD shall not be hazardous live. The part or contact of a terminal of the DVB-T2 IRD is hazardous live if the open-circuit voltage exceeds 35 V peak (AC) or 60 V DC.
- (b) DVB-T2 IRD is not subject to overvoltage from telecommunication networks⁴.

4.2.2.3 For DVB-T2 IRD safety assessment performed with hazard-based approach, the processes defined in IEC 62368-1 [5] shall be used:

- (a) Identify energy sources in the DVB-T2 IRD;
- (b) Classify energy sources (effect on the body or combustible material, e.g. possibility of injury or ignition);
- (c) Identify safeguards for protection against energy sources; and
- (d) Consider the effectiveness of safeguards with respect to compliance criteria or requirements defined in the standard [5].

⁴ Manufacturers, when designing ICT equipment or network devices for use in home environments according to IEC 60065 [4] or IEC 62368-1 [5], may assume that customer buildings or premises meet the qualifying conditions for equipment resistibility to overvoltage up to 1.5 kV. There should be overvoltage protection installed at the network and power termination points together with earthing and bonding techniques (according to ITU-T K.66 for protection of customer premises from overvoltage).

5 Use of Video and Audio Coding in Broadcasting Applications based on the MPEG-2 Transport Stream

5.1 Transport Stream Bit-streams

- 5.1.1 The DVB-T2 IRD shall comply with implementation guidelines outlined in § 4 of ETSI TS 101 154 [1], based on the MPEG-2 Transport Stream bit-streams requirements defined in § 2.4 of ITU-T Rec. H.222.0 / ISO/IEC 13818-1 [10].
- 5.1.2 The DVB-T2 IRD shall be able to de-multiplex and present programs according to the Program Specific Information (PSI) defined in § 2.4 of ITU-T Rec. H.222.0 / ISO/IEC 13818-1 [10].
- 5.1.3 The Transport Stream supports the multiplexing of video and audio compressed streams from one program with a common time base or from multiple programs with independent time bases. Programs are composed of one or more elementary streams, each labelled with a Packet Identifier (PID). The DVB-T2 IRD shall be able to handle simultaneously at least 32 PIDs and elementary streams.
- 5.1.4 The DVB-T2 IRD shall be able to skip over data structures which are currently "reserved" (§ 4.1 of ETSI TS 101 154 [1]).
- 5.1.5 The DVB-T2 IRD shall operate over the full tolerance range of the system clock frequency as specified in § 2.4.2.1 of ITU-T Rec. H.222.0 / ISO/IEC 13818-1 [10].
- 5.1.6 The DVB-T2 IRD shall operate correctly with Program Clock References (PCRs) for a program arriving at intervals not exceeding 100 ms as specified in § 2.7.2 of ITU-T Rec. H.222.0 / ISO/IEC 13818-1 [10].

5.2 Video Decoding

- 5.2.1 The DVB-T2 IRD shall comply with the implementation guidelines outlined in § 5.1 of ETSI TS 101 154 [1] for decoding MPEG-2 video. The DVB-T2 IRD shall be able to decode video formats as specified in Table 1, based on the ITU-T Rec. H.262 / ISO/IEC 13818-2⁵ [11].

DVB-T2 IRD	Bit-stream	Frame Rate	Aspect Ratio	Luminance Resolution
25 Hz MPEG-2 SDTV (§ 5.1 of ETSI TS 101 154)	MP@ML	25 Hz interlaced	4:3 or 16:9 Use of pan vectors and up sampling	720 x 576 Capable of decoding lower picture resolutions

Table 1: Video decoding to ITU-T Rec. H.262 / ISO/IEC 13818-2

⁵ Please note that such video formats may be intellectual property of third parties.

- 5.2.2 The DVB-T2 IRD shall comply with the implementation guidelines outlined in § 5.5, § 5.6 and § 5.7 of ETSI TS 101 154 [1] for decoding H.264/AVC video. The DVB-T2 IRD shall be able to decode video formats as specified in Table 2, based on the ITU-T Rec. H.264 / ISO/IEC 14496-10⁶ [12].

DVB-T2 IRD	Bit-stream	Frame Rate	Aspect Ratio	Luminance Resolution
25 Hz H.264/AVC SDTV (§ 5.6 of ETSI TS 101 154)	HP@L3	25 Hz interlaced	4:3 or 16:9 Frame cropping	720 x 576 Capable of decoding lower picture resolutions
50 Hz H.264/AVC HDTV With backward compatibility (§ 5.7 of ETSI TS 101 154)	HP@L4	50 Hz progressive	16:9 Up sampling	1280 x 720
25 Hz H.264/AVC HDTV	HP@L4	25 Hz interlaced	16:9 Up sampling	1920 x 1080
25 Hz H.264/AVC HDTV	HP@L4	25 Hz progressive (Optional)	16:9 Up sampling	1920 x 1080

Table 2: Video decoding to ITU-T Rec. H.264 or ISO/IEC 14496-10

5.2.3 Aspect Ratio

The DVB-T2 IRD shall provide convenient user control for appropriate aspect ratio switching between 4:3 and 16:9 to adapt to display in different size and aspect ratio.

5.2.4 Active Format Description (AFD)

When AFD is used, the DVB-T2 IRD shall present the video aspect ratio properly according to the current AFD value and response in next frame as defined in the ETSI EN 101 154 Annex B. The DVB-T2 IRD shall support at least the Active Formats shown in Table 3.

Refer to Annex A for the illustration on the required outputs based on the AFD values specified in Table 3.

Active Format	Aspect ratio of the "area of interest"
1000	Active format is the same as the coded frame.
1001	"Pillar box" 4:3 (centre)
1010	"Letter box" 16:9 (centre)

Table 3: Active format (Table B.5/ETSI TS 101 154)

⁶ Please note that such video formats may be intellectual property of third parties.

5.3 Audio Decoding

5.3.1 MPEG-1 Layer II Audio⁷

5.3.1.1 The DVB-T2 IRD shall comply with the implementation guidelines outlined in § 6.1 of ETSI TS 101 154 [1] for decoding MPEG-1 Layer II audio, based on ISO/IEC 13818-3 [13] in single (mono), dual, joint stereo and stereo modes with bit rates between 64 kbit/s and 256 kbit/s, and sampling rates of 32 kHz, 44.1 kHz and 48 kHz.

5.3.1.2 The DVB-T2 IRD shall provide convenient user control for appropriate audio output format switching between different audio modes.

5.3.2 MPEG-4 HE-AAC Version 2 Audio (Level 4)⁸

The DVB-T2 IRD shall comply with the implementation guidelines outlined in § 6.4 and Annex C5 of ETSI TS 101 154 [1] for decoding MPEG-4 HE-AAC version 2 audio Level 4 and sampling rates of up to 48 kHz, based on ISO/IEC 14496-3 [14]. The DVB-T2 IRD shall apply bit-stream metadata parameters and down-mix multi-channel input configurations to stereo PCM.

5.3.3 Decoding & Presentation Options for 2 Channels of Decoder Output

Codec	Analogue Output / Speaker (IDTV)	Optical / Coaxial (S/PDIF) / HDMI ARC output**	HDMI*
MPEG-1 Layer II	Mono / Stereo	PCM stereo	PCM stereo
MPEG-4 HE-AAC	Mono / Stereo	PCM stereo Pass through of HE-AAC bit stream (Optional)	PCM stereo Pass through of HE-AAC bit stream (Optional)

Note: * Only applicable to DVB-T2 IRD with HDMI output

** Only applicable to DVB-T2 IRD with S/PDIF or HDMI ARC output

Table 4: Presentation Options for 2 Channels of Decoder Output

5.3.4 Audio handling when changing service or audio format

The DVB-T2 IRD should gracefully handle change of service or audio format at the audio outputs without significant disturbances to the end user.

5.3.5 Lip-Sync (Recommended)

For all supported formats of audio, the maximum timing misalignment between audio and video in reference with Program Clock Reference (PCR) - time stamp carried by video should be confined within ± 20 ms.

5.3.6 Loudness Matching (Optional)

The DVB-T2 IRD should apply format dependent attenuation to decoded stereo PCM audio, in order to achieve loudness alignment between different input formats.

⁷ Please note that such audio formats may be intellectual property of third parties.

⁸ Same as footnote 7

5.3.7 Audio Description

The DVB-T2 IRD shall support audio description in Broadcast-mix mode according to Annex E of ETSI TS 101 154 [1].

5.3.8 Audio Prioritising

The DVB-T2 IRD shall apply audio prioritising in the following order:

- User preferred audio language selection
- First Audio appeared in the elementary stream loop of the Program Map Table (PMT) or the stream having the lowest PID value

If a service offers both multichannel and stereo audio, the DVB-T2 IRD shall continue to apply the priority as described above.

If the DVB-T2 IRD supports prioritising based on OSD language or country's default language, then the following audio prioritising applies:

- Audio streams signalled as English (ENG), Chinese (ZHO), Bahasa Melayu (MSA) and Tamil (TAM) shall have equal priorities.
- Audio streams signalled as English (ENG), Chinese (ZHO), Bahasa Melayu (MSA) and Tamil (TAM) shall have equal or higher priorities over the other languages defined in § 7.3 Multi-Language Support of Part A of the TS DVB-T2 IRD.

6 Frontend Characteristics

6.1 General Considerations

The DVB-T2 IRD shall be compatible with the DVB-T baseline system according to the ETSI EN 300 744 [3] and the DVB-T2 baseline system according to the ETSI EN 302 755* [2] for digital terrestrial TV (DTT), and able to receive DTT services in the existing VHF and UHF spectrum allocation for analogue transmissions. It is required that the DVB-T/T2 system will provide sufficient protection against high levels of Co-Channel Interference (CCI) and Adjacent Channel Interference (ACI) emanating from existing PAL and digital TV services.

Note: * Support for DVB-T2 Lite is optional

Transmission Frequencies and Signal Bandwidths

Band	Frequency Range	Signal Bandwidth
VHF III	174 – 230 MHz	7 MHz
UHF IV	470 – 606 MHz	8 MHz
UHF V	606 – 862 MHz	8 MHz

Table 5: Mandatory Frequency Bands

6.2 Maximum Frequency Offset

The DVB-T2 IRD shall be able to receive signals with an offset of up to $\pm 1/6$ MHz from the nominal frequency.

6.3 Operating Modes

6.3.1 The DVB-T2 IRD shall be able to demodulate all non-hierarchical modes specified in the ETSI EN 300 744 [2]. The frontend shall work compatibly with any combination of constellation (QPSK, 16-QAM OR 64-QAM), code rate (1/2, 2/3, 3/4, 5/6 or 7/8), guard interval ($T_U/4$, $T_U/8$, $T_U/16$, or $T_U/32$) and transmission mode (2k or 8k).

6.3.2 The DVB-T2 IRD shall be able to detect which DVB-T2 mode is being used. The DVB-T2 parameters or modes are outlined in Table 6.

DVB-T2 Parameter/Mode	Requirement
Constellation	QPSK, 16-QAM, 64-QAM or 256-QAM With or without constellation rotation
Code Rate	1/2, 3/5, 2/3, 3/4, 4/5 or 5/6
Guard Interval	$T_U/128$, $T_U/32$, $T_U/16$, $T_U*19/256$, $T_U/8$, $T_U*19/128$ or $T_U/4$
Transmission Mode (Fast Fourier Transform, FFT size)	1k, 2k, 4k, 8k normal, 8k extended, 16 normal, 16k extended, 32k normal or 32k extended
Pilot Pattern (PP)*	PP1, PP2, PP3, PP4, PP5, PP6 or PP7
Antenna	SISO or MISO
Signalling format for Peak Average Power Ratio (PAPR) reduction	L1-ACE is used and TR is used on P2 symbols only; L1-ACE and ACE only are used; L1-ACE and TR only are used; or L1-ACE, ACE and TR are used.
Forward Error Correction (FEC) Frame Length	64 800 bits for normal FECFRAME; 16 200 bits for short FECFRAME
Input Mode	'A' (single PLP) or 'B' (multiple PLPs)
Mode Adaptation	Normal Mode (NM); or High Efficiency Mode (HEM)
Scrambling of L1 post signalling (L1_POST_SCRAMBLED)	Feature shall be supported by the DVB-T2 IRD.

Note: *Support for Pilot Pattern 8 is optional

In addition, support for time frequency slicing (TFS) is not required for the DVB-T2 IRD with single front-end/tuner.

Table 6: DVB-T2 Parameters/Modes

6.4 DVB-T2 Performance Requirements

The performance requirements of the DVB-T2 IRD shall be measured according to the list modes outlined in Annex E.

6.5 Performance in Time-Varying Channels

The increase in required C/N for QEF reception shall be less than 3 dB for a 0 dB echo with frequency separation equal to 10 Hz and a delay of 20 μ s, corresponding to a Doppler shift of +/- 5 Hz (after AFC), compared to a 0 dB echo with frequency separation equal to 1 Hz and a delay of 20 μ s, corresponding to a Doppler shift of +/- 0.5 Hz (after AFC).

6.6 Operation in Single Frequency Network (SFN)

The DVB-T2 IRD shall be able to operate in SFN with echo signals within the guard interval. When the DVB-T2 IRD tunes to a mix of two signals from a SFN where the received signals are close in amplitude, it is recommended that the DVB-T2 IRD selects the best signal.

7 Service Information (SI)

7.1 Use of DVB Service Information (SI)

In addition to the PSI defined in § 2.4 of ITU-T Rec. H.222.0 / ISO/IEC 13818-1 [10], the DVB-T2 IRD shall be able to decode the SI data in the Transport Stream bit-streams which provides users with information to select services so that the DVB-T2 IRD can automatically configure itself for the selected service. The DVB-T2 IRD shall comply with the implementation guidelines outlined in the ETSI TR 101 211 [15] for the use of DVB SI as specified in the ETSI EN 300 468 [16]. The SI table mechanism, syntax and semantics, and minimally, the Service Description Table (SDT), the Event Information Table (EIT) and the Time and Date Table (TDT) shall be supported.

7.2 System Timing

The DVB-T2 IRD shall make use of Time and Date Table (TDT) for the device system time or Real Time Clock (RTC) setting.

7.3 Optional and Unrecognised SI (Optional)

For DVB-T2 IRD with recording features, it is recommended that Selection Information Table (SIT) be supported for partial transport stream selection and recording. Support of Bouquet Association Table (BAT), Stuffing Table (ST) and Data Information Table (DIT) is optional. The DVB-T2 IRD shall ignore any incomprehensive SI or tables. The DVB-T2 IRD shall discard any PSI/SI signals if it is unrecognised or not supported.

7.4 PSI/SI and PID Update

The DVB-T2 IRD shall be able to monitor and update all PSI with shorter than 100 ms interval and all SI with less than 1000 ms interval. The DVB-T2 IRD shall update PSI / SI information in memory whenever any update or modification happens on a real-time basis. The DVB-T2 IRD shall take prompt action with changes or modifications on the parameters of transmissions, networks and services.

7.5 Dynamic Response to PAT, PMT, NIT and SDT Updates

The DVB-T2 IRD shall be capable to identify changes or new services in the current channel/multiplex.

7.6 Service Identification and Logical Channel Number (LCN)

The DVB-T2 IRD shall be able to automatically scan through the whole frequency range available for each of the available Tuners/Demodulators and tune in to the correct DVB framing structure, channel coding and modulation to deliver the incoming transport stream to the next units. The tuning data shall be stored to allow a quick tune in to the selected transport stream.

The DVB-T2 IRD shall support LCN by using descriptor with tag value is 0x83 (Version 1) and 0x87 (Version 2). All services shall be sorted, listed and managed accordingly with assigned LCN. In case duplicated and conflicted LCNs are found, shall be given to services with better signal quality, other services shall be arranged to reserved LCN range.

The channel map shall be from 1-999 with valid LCN's is being assigned in the range from 1-799 by the broadcaster (Contain all types of services including Radio/Data/Video). The LCN reserved range is set from 800 – 999.

The following DVB identification values shall be used for digital terrestrial transmission.

Identifier	Value
Private Data Specifier	0x00000019
Original Network ID	0x22BE

Broadcaster will be assigned with the logical channel numbering (LCN) range for terrestrial FTA channels to facilitate easy access to these channels. For example, by pressing '2' on remote control will allow user to switch to Channel 5, '3' to switch to Channel 8 (See Annex F for the proposed Channel Numbering Range for FTA channels.)

7.6.1 Logical Channel Numbering (LCN)

The intention of the LCN service information is to provide a broadcaster assigned virtual channel number or label, for each of the available DTV services to the DVB-T2 IRD, so the DVB-T2 IRD is able to easily facilitate the channel sorting, indexing, ordering, and searching. The LCN descriptor also defines visibility of the service to the viewer.

The syntax and semantics of the logical_channel_descriptor is indicated in Table 7 below, as follows:

Syntax	Bits	Identifier
logical_channel_descriptor(){		
descriptor_tag	8	uimsbf
descriptor_length	8	uimsbf
for (i=0;i<N;i++){		
service_id	16	uimsbf
visible_service3_flag	1	bslbf
reserved	5	bslbf
logical_channel_number	10	uimsbf
}}		

Table 7: Syntax and Semantics of the Logical Channel Descriptor

descriptor_tag: This shall be assigned to be 0x83.

service_id: This is a 16-bit field which serves as a label to identify this service from any other service within the Transport Stream. The service_id is the same as the program_number in the corresponding program_map_section. Services shall be included irrespective of their running status.

visible_service_flag:

- = 1: The service is visible and selectable via the DVB-T2 IRD service list.
- = 0: The service is invisible and not selectable via the DVB-T2 IRD service list, however the DVB-T2 IRD may provide a mechanism to access these services.

reserved: This 5-bit field is reserved for future use, shall be set to "1".

logical_channel_number: This is a 10-bit field which indicates the broadcaster preference for ordering service.

The channel map shall be from 1-999. A broadcaster may or may NOT allocate more than one Logical Channel Number to a service. This is to avoid multiple LCN assignment which could lead to cross reference and confusion.

7.6.2 Logical Channel Descriptor (Version 2)

The syntax of the Logical Channel Descriptor (version 2) is shown in below Table 8.

Syntax	No. of bits	Identifier
Logical_channel_descriptor(){	8	Uimsbf
descriptor_tag	8	Uimsbf
descriptor_length for	8	Uimsbf
(i=0;i<N;i++){	8	Uimsbf
channel_list_id	8	Uimsbf
channel_list_name_length	8	Uimsbf
for (i=0;i<N;i++) {	24	Uimsbf
char	8	Uimsbf
}		Bslbf
country_code	16	Bslbf
descriptor_length		Uimsbf
for (i=0;i<number_of_services;i++){	1	
service_id	5	
visible_service_flag	10	
reserved_future_use		
logical_channel_number		
}		
}		
}		

Table 8: Syntax and Semantics of the Logical Channel Descriptor (Version 2)

descriptor_tag: This shall be assigned to be 0x87 (decimal 135).

channel_list_id: This is an 8-bit field which serves as a label to identify the channel list (uniquely allocated within each original_network_id).

When several Channel Lists are available from same network (original network id) and same country code for the IRD during first time installation (or complete re-installation), the receiver shall choose the channel list as the default one with following priority:

The IRD shall choose the one with lowest list_id value OR let the viewer choose from a list, (typically using the channel_list_name)

channel_list_name_length: This 8-bit field specifies the number of bytes that follow the channel_list_name_length field for describing characters of the name of the Channel List. Maximal length is 23 bytes for the channel_list_name.

char: This is an 8-bit field. A string of character fields specify the name of the channel list, the channel_list_name. (Maximal length is 23 bytes for the channel_list_name). Text information is coded using the character sets and methods described in EN 300 468 [13].

country_code: This 24-bit field identifies a country using the 3-character code as specified in ISO/IEC 3166 [14]. Each character is coded into 8-bits according to ISO/IEC 8859-1[15] and inserted in order into the 24-bit field. This shall be set to "SGP".

service_id: A service_id that belongs to the Transport Stream (i.e. services from other Transport Stream shall not be listed). One service may only be listed once in each channel list, but may belong to/be listed in more than one channel list.

visible_service_flag: This 1-bit field when set to '1'/'true' indicates that the service is normally visible and selectable (subject to the service type being suitable etc.) via the DVB-T2 IRD's service list. When set to '0'/'false' this indicates that the DVB-T2 IRD is not expected to offer the service to the user in normal navigation modes however the DVB-T2 IRD should provide a mechanism to access these services (for example by direct entry of the logical channel number).

Reserved: All "reserved" bits shall be set to '1' (observe, however, that the DVB-T2 IRD shall be able to handle (neglect) future use of reserved bits).

logic_channel_number: The channel map shall be from 1-999 with valid LCN's is being assigned in the range from 1-799 by the broadcaster (Contain all types of services including Radio/Data/Video).

7.6.3 Logical Channel Descriptor Simultaneous Version 1 and Version 2 Transmissions

When both Logical Channel Descriptor version 1 and version 2 are broadcasted within one Original Network ID, the DVB-T2 IRD supporting both descriptors shall only sort according to the version 2 (higher priority).

7.6.4 Listing of Broadcast Descriptors

The list of broadcast descriptors is attached in Annex G.

8 Services

8.1 Subtitling

8.1.1 Specification for Subtitling

The DVB-T2 IRD shall support DVB subtitling in accordance with ETSI EN 300 743 [19], and displayed using the On Screen Display (OSD) capabilities while decoding the full television service (video and audio). The subtitle object code shall be handled as pixels (bitmap).

8.1.2 Multiple Subtitling Language

The DVB-T2 IRD shall be able to handle multiple subtitling streams within the same service and the correspondent PSI/SI information like languages descriptors.

The receiver shall provide convenient user control for enabling, disabling displaying and to select primary and secondary subtitling languages.

In case of subtitling is set to "ON" and the subtitle streams do not match any of the settings of preferred languages, the receiver shall select the first subtitle stream signaled in the elementary stream loop of the PMT.

The recommended factory default setting:

The default setting on the receiver for subtitling set to "ON"
The primary preferred language set to "Multiple Languages" (MUL)
The secondary preferred language set to "Multiple Languages" (MUL)

8.1.3 Support for hearing impaired

The DVB-T2 IRD shall have user selection of subtitling preferences for 'normal' or 'hard of hearing' subtitles.

In case of 'hard of hearing' subtitling mode is selected and if no 'hard of hearing'/'hearing impaired' pages are received (signalled in subtitling descriptor), then the receiver shall as a default use 'normal' subtitling pages from the same selected language.

8.2 Electronic Program Guide (EPG)

8.2.1 Specification for EPG

The DVB-T2 IRD shall decode full EIT information with capability to display "present / following" (or "Now / Next") and schedule EPG information in accordance with guidelines given in ETSI TR 101 211 [12] and requirements defined in ETSI EN 300 468 [16].

The receiver shall also be able to continue to operate in the absence of EIT transmission.

8.2.2 EPG Presentation

EPG presentation shall include but not limited to the followings:

- a) service name
- b) program title
- c) program duration
- d) elapsed duration (optional)
- e) short description
- f) long description (extended text)
- g) present / following (now / next) event

- h) current date/time
- i) parental guidance information

The receiver shall provide an EPG organizer to access Next seven-day program guide with all information in above list. It should be a practical and easy to use search function.

8.2.3 Languages and Fonts

For EPG and other labeling decoding and presentation, the receiver shall support the character coding tables specified in below table:

Font	Coded Character Set	First byte value
Latin	ISO 6937	N/A
Chinese	GB18030-2005	0x11 and 0x15
Tamil (Optional)	Unicode range U+0B80-U+0BFF	0x11 and 0x15

Note:

- a) The first byte value is signalled according to ETSI EN 300 468 Annex A [1].
- b) GB18030-2005 characters are broadcasted as ISO 10646 UTF-16 or UTF-8 code points. The receiver is not required to support code points beyond the Basic Multilingual Plane.

Multi-Language Support for EPG presentation

The DVB-T2 IRD shall support EPG presentation signalled with ENG, ZHO and MSA by offering a means to select the EPG language.

It is optional to support EPG presentation signalled with TAM.

When EPG data is offered in multiple languages, it is recommended that the DVB-T2 IRD provides an easy to use option to allow the user to select the language for EPG presentation.

When the user preferred language for EPG presentation does not match any languages that are available, it is recommended to select the language of the First EPG data (Short Event Descriptor) appeared in the descriptor loop of the Event Information Table (EIT).

It is recommended to support the `multilingual_service_name_descriptor`. When `multilingual_service_name_descriptor` is present and the user preferred language for EPG presentation does not match any languages that are available, it is recommended to select the first service name appeared in said descriptor.

It is recommended to allow the user to toggle the languages when viewing the EPG presentation.

8.2.4 Parental Lock Feature

The DVB-T2 IRD shall have parental lock capabilities to block television program with a particular Classification Code from being shown unless the correct personal identification number (PIN) code is entered by the user.

The DVB-T2 IRD must be able to identify the Classification Code that is applied to the television program and shall allow user to set the rating that he/she wants to block.

The matrix table which shows the list of Classification Code and their assigned hexadecimal code is attached in Annex C.

The Classification Codes are defined as follows:

- a) General (G) – Suitable for all ages;
- b) Parental Guidance (PG) – Suitable for all, but parents should guide their young;
- c) Parental Guidance 13 (PG13) – Suitable for persons aged 13 and above but parental guidance is advised for children below 13;
- d) No Children Under 16 (NC16) – Suitable for persons aged 16 and above;
- e) Mature 18 (M18) – Suitable for persons aged 18 and above; and
- f) Restricted 21 (R21) – Restricted to persons aged 21 and above.

8.2.5 Parental Rating Display

The parental rating information shall be displayed clearly as part of EPG.

The parental rating descriptor shall be transmitted and the full parental rating information shall be appended to the front of the program title or program description by the broadcaster. Manufacturers can add additional displays of programme ratings, but they must display the full rating information.

8.3 Multi-Language Support

The DVB-T2 IRD shall provide a mechanism for the selection of primary and secondary language options for both subtitles and audio selection. The receiver shall as a minimum, interpret the language codes outlined in the table below.

Language	ISO 639-3 Code
English	eng
Chinese	zho
Bahasa Melayu	msa
Tamil	tam
Original Audio	qaa
Second Audio	qab*
Third Audio	qac*
Multiple Languages	mul

Note:

- a) Original, Second and Third Audio are only applicable for Audio
- b) Multiple Languages is only applicable for Subtitle
- c) ISO 639 language codes shall be case-insensitive
- d) *Optional for IRDs that are launched before 2015

When the audio streams are not signalled with ISO 639 Language Descriptor, the DVB-T2 IRD shall continue to indicate the presence of the audio streams and provide a mechanism for the user to select such streams.

8.4 Teletext (Optional)

The DVB-T2 IRD should be able to demultiplex in parallel the Teletext service transmitted in a packetised format according ETSI EN 300 472 [20]. Where available, the DVB-T2 IRD shall be able to display Teletext service, meeting the requirements for at least Level 1.5 in ETSI EN 300 706 [21] - Enhanced Teletext specification.

8.5 Remote Control Interface

A Remote Control shall be bundled with the DVB-T2 IRD. It should be simple and easy to use. Basic functionality such as power, volume control and numerical number 0-9 shall be placed on prominent locations on the remote control. Colour-coded multifunctional buttons shall be included to enhance user experience and ease the navigation on the receivers.

The list of basic and digital TV function keys is attached in Annex D.

9 Interfaces and Connectors

9.1 RF Input Connector

The DVB-T2 IRD shall have one input tuner connector, type: IEC female in accordance with IEC 61169-2, part 2 [22]. The input impedance shall be 75 ohm.

9.2 RF Output Connector

The DVB-T2 IRD without an integrated display should provide a connector with a loop-through of input RF signal.

- a) The connector shall be of type: IEC male in accordance with IEC 61169, part 2 [22].
- b) The frequency range for the RF loop-through should be from 47 MHz to 862 MHz.
- c) The RF loop-through signal shall be present independently from the status of the DVB-T2 IRD device (operational or standby), such that that connected equipment (e.g. TV set) can operate even if the device is in standby mode.
- d) When the RF bypass gain is disabled, the maximum RF bypass gain should -4dB and when the RF bypass gain is enabled, the RF bypass gain should be from -1 dB to +3 dB.

9.3 Modulator output (Optional)

The DVB-T2 IRD without an integrated display should provide a re-modulated output for use with a PAL receiver. If so, the output must be tuneable to any of UHF channels 21 to 68. The peak signal level should be 3 mV nominal across 75 ohm (-39 dBm).

9.4 Antenna Output Power (Optional)

It is optional for the receiver to provide 5V DC output for the active antenna power supply. If it is provided, the 5V DC shall be able to be turned on/off.

9.5 Component Analogue Outputs (Optional)

It is optional for the receiver to provide component analogue output (YPbPr).

9.6 Composite Video Outputs

For DVB-T2 IRD (standalone module) the composite video output shall comply with PAL Connector IEC 48B Section 316 (RCA- phono).

9.7 Additional Requirements for Composite Video Interface (Optional)

For the analogue outputs, the DVB-T2 IRD (standalone module) should also support insertion of the teletext data in the VBI of the analogue CVBS video output. In this case, the teletext decoder of the TV-set may be used instead of the one in the IRD, and the VBI insertion shall be compliant with ITU-R BT.653-3 [23]. Where available, the Teletext data shall be inserted in the lines 7 to 22 and lines 320 to 335.

9.8 Analogue Audio

The DVB-T2 IRD (standalone module) shall provide RCA-phono output interface for analogue stereo audio.

9.9 Digital Audio Data Stream Output (S/PDIF) or HDMI Audio Return Channel (Optional)

It is optional for the DVB-T2 IRD to provide the following interface:

- a) S/PDIF digital audio output – electrical (coaxial) or optical (TOSLINK); or
- b) HDMI Audio Return Channel (HDMI ARC).

The capabilities of this interface are defined in § 4.3.3 of Part A and § 5 of Part B of this document.

9.10 HDMI⁹

The DVB-T2 IRD (standalone module) shall provide HDMI interface for digital video and audio output.

9.11 Copy Protection on Outputs

The DVB-T2 IRD (standalone module) shall provide High Bandwidth Digital Content Protection (HDCP) on the HDMI output for all output resolutions.

If the DVB-T2 IRD is capable of recording broadcast services in persistent memory¹⁰, then all recordings shall be stored in a protected format. The DVB-T2 IRD shall not allow for the extraction or output of the recorded content in unprotected digital format.

9.12 Common Interface (Optional)

The DVB-T2 IRD may incorporate a DVB-CI (Common Interface) slot. If available this slot shall be a certified CI+ slot as outlined in CI+ specification V1.3 meeting all the required robustness rules.

⁹ Please note that such multimedia interface for transferring data may have intellectual property of third parties.

¹⁰ Persistent memory refers to non-volatile storage like Hard Disk Drive (HDD) or flash drive.

10 Firmware Operation

10.1 Operating System and Memory

The DVB-T2 IRD shall have an embedded real time operating system. It shall include a non-volatile memory for retaining user settings and other data.

10.2 First-time Power Up

Upon powering up for the first-time, the DVB-T2 IRD shall initiate the following process:

- a) Set OSD language (Default – English);
- b) Set active antenna power [if available] (Default – Off,);
- c) Prompt tuning/scanning for all available FTA services; and
- d) Set other configurations (user data, preferences, etc).

10.3 Initial Channel Scan

The tuning/ scan process should be manually initiated to prevent scanning before the antenna is connected.

The DVB-T2 IRD shall do a full scan of all available services in all the TV broadcast bands starting with VHF TV Band III to UHF Band. The DVB-T2 IRD's scan process shall include all possible combinations of OFDM parameters until the transmission parameters are found.

10.4 Subsequent Power On

The DVB-T2 IRD shall return either to last watched or preset start-up service.

10.5 Listing of all available services

The DVB-T2 IRD shall provide a listing of all available FTA services after scanning.

10.6 Responses to Network Changes

10.6.1 Addition of multiplex on a network

When a multiplex is added to the network, it shall make reference in the second loop of the NIT actual table. The NIT (actual) version_number shall be changed. The DVB-T2 IRD shall recognise the change of version_number of the NIT table and that a new transport_stream_id is present in the NIT (actual). The DVB-T2 IRD shall response to the network changes by performing a rescan or adopting an appropriate method to notify the user to perform a rescan.

10.6.2 Addition or removal of service on a multiplex

When a service has been added to a multiplex, there shall be an update in the SDT (actual) for that multiplex which references the new service.

The DVB-T2 IRD shall consider a service to be removed from a multiplex if the service is not referenced in the SDT (actual) of that particular service.

A rescan of any or all the terrestrial multiplexes shall not be required for the DVB-T2 IRD to acknowledge the presence of a new service. The DVB-T2 IRD shall consider a service is added to a multiplex if the new service is referenced in the SDT (actual).

When a new service is added or removed from a multiplex, the DVB-T2 IRD may inform the user that a new service has been added or removed using an appropriate DVB-T2 IRD specific method e.g. a short screen pop-up lasting not more than 3 seconds.

10.6.3 Transmission mode change

In the event that there is any transmission mode changes, the DVB-T2 IRD shall automatically perform update to capture these changes without disruption to the viewer.

10.6.4 Clash resolution

The DVB-T2 IRD shall base on the PDS (Private Data Specifier) before assigning LCN to the services and put other services (if any) with the same LCN from undefined PDS to 'reserved' LCN range.

10.7 Signal strength and quality bar

The DVB-T2 IRD shall be able to display both signal strength and quality (BER) level. This will aid the user in setting up indoor antenna to ensure best reception position or identifying other reception problems.

10.8 Service unavailability

In the event of service unavailable, poor or no RF signal, the DVB-T2 IRD shall display an on-screen message.

10.9 Hardware reset / reboot / factory default setting

The DVB-T2 IRD shall support hot reset, cold reset, and a full reset to manufacturer's default start-up settings.

10.10 Channel zapping time

The channel zapping time between channels within same multiplex shall be between 1.5 to 3 seconds. It shall be met for a GOP length of 12, and a repetition rate of PAT and PMT of 10 tables per second. Interruption to viewer during channel zapping shall be kept at minimal.

10.11 System software update (SSU/OTA/OAD)¹¹

The DVB-T2 IRD shall be able to support Over-The-Air firmware upgrade by using System Software Update mechanism in accordance with the ETSI TS 102 006 [24]. The DVB-T2 IRD shall automatically detect and invoke OTA (SSU) service by recognized Organization Unique Identifiers (OUI) in the NIT linkage with type value as 0x9. The DVB-T2 IRD shall at least support DVB-SSU simple profile.

The default DVB-SSU mode for DVB-T2 IRDs shall be with DVB-SSU "enabled".

10.12 User system software upgrade

The DVB-T2 IRD shall provide one or more of the following data interfaces to enable the user to perform software upgrades.

- a) Universal Serial Bus (USB)
- b) RJ 45 (Ethernet IEE802.3)
- c) Appropriate Memory Card

¹¹ Manufacturers/suppliers may provide other means of performing the software upgrade for DVB-T2 IRDs that are distributed for commercial use.

Part B Additional DVB-T2 IRD Requirements for supporting Multi-Channel Audio

Multi-channel Audio

1 Format

The DVB-T2 IRD shall identify, accept and decode input bit-streams in the following formats:

- a) E-AC3 as specified in ETSI TS 102 366¹² [25]; and
- b) MPEG-4 HE-AAC version 2 Level 4 as defined in ISO/IEC 14496-3¹³ [14]

2 Metadata

The DVB-T2 IRD shall apply bit-stream metadata parameters and down mix multi-channel input configurations to stereo PCM for Enhanced AC-3 in accordance with guidelines given in ETSI TS 102 366 [25] and MPEG-4 HE-AAC as specified in ISO/IEC14496-3 [14] and ETSI TS 101 154 [1].

3 Pass-through

The DVB-T2 IRD shall pass through the native audio elementary input bit-stream over the HDMI output for standalone module or ARC output for DVB-T2 IRD (where applicable) as well as the optical/coaxial output (where applicable).

4 Trans-coding

The DVB-T2 IRD shall trans-code audio and metadata from E-AC3 input bit-streams to AC-3 output bit-streams at a data rate of 640kbps. The DVB-T2 IRD shall transcode audio and metadata from MPEG-4 HE-AAC input bit-streams to an AC-3 output bit-stream at a data rate of 640kbps or alternatively to a DTS output bit stream at a data rate of 1.5 Mbps. The number of channels on the output AC-3 or DTS bit-stream shall be equal to or greater than the number of channels contained within the input bit-stream. The AC-3 or DTS bit-stream shall be provided over the following outputs:

- a) S/PDIF; and
- b) HDMI output for standalone module or ARC output for DVB-T2 IRD (where applicable).

¹² Please note that such audio formats may be intellectual property of third parties.

¹³ Same as footnote 9

5 Decoding & Presentation Options for Multi-Channel Decoder

Codec	Analogue Output / Speaker (IDTV)	Optical / Coaxial (S/PDIF)/ HDMI ARC output **	HDMI*
E-AC3 multi-channel	Down-Mixed Stereo	Trans-code to AC-3 bit-stream and pass through PCM stereo	Pass through of E -AC3 bit-stream Trans-code to AC-3 bit-stream and pass through PCM stereo and multi-channel
MPEG-4 HE-AAC multi-channel	Down-Mixed Stereo	Trans-code to AC-3 or DTS bit-stream and pass through PCM stereo Pass through of HE-AAC bit stream (Optional)	Pass through of HE-AAC bit-stream (Optional) Trans-code to AC-3 or DTS bit-stream and pass through PCM stereo and multi-channel

Note: * Only applicable to DVB-T2 IRD with HDMI output
 ** Only applicable to DVB-T2 IRD with S/PDIF/ HDMI ARC output

Table 9: Presentation Options for Multi-Channel Decoder

6 Audio Description (Optional)

The DVB-T2 IRD should support audio description in Receiver-mix mode according to Annex E of ETSI 101 154 [1].

Where available, the audio description service shall be provided as an associated service in a separate stream encoded with the same audio codec as used for the main program.

In case of the use of E-AC3 as audio codec, the mixing data shall be included as part of the E-AC3 bit stream as defined in ETSI TS 102 366 Annex E [25] and the AD_descriptor defined in ETSI TS 101 154 Annex E.2 [1], if present, shall be ignored.

Part C Exceptions for other DVB-T2 IRD Implementations

Parts A and B of this Specification define the minimum requirements for Set-Top-Box (STB) and Integrated Digital Television (IDTV). Part C of this Specification sets out the exceptions to the Part A requirements to which other DVB-T2 IRD implementations, such as PC cards, dongles, portable TV or similar devices, may not need to comply.

Such IRD implementations are required to comply with the minimum requirements defined in Part A, with the exception of those outlined in Table 10.

Note: The word “Recommended” means this item is not mandatory but is highly recommended. If included it should then be implemented as specified in Part A of the Specification.

Part A: Basic DVB-T2 IRD Requirements	Description of Exceptions
§5.2.4: Active Format Description (AFD) ¹⁴	It is recommended to comply with this requirement.
§7.6: Service Identification (SI) and Logical Channel Number (LCN) ¹⁵	It is recommended to comply with this requirement.
§8.2: Electronic Program Guide (EPG)	It is recommended to comply with this requirement.
§8.2.1: Specification for EPG	
§8.2.2: EPG Presentation	
§8.2.3: Languages and Fonts	
§8.2.4: Parental Lock Feature	
§8.2.5: Parental Rating Display	
§9: Interfaces and Connectors	Different RF input connector may be used where appropriate. RF output connector (§9.2) is optional, and may be included where appropriate. Requirements of various output interfaces are optional, and may be included where appropriate (§9.6, §9.8 and §9.10).
§10.11: System Software Update (SSU/OTA/OAD)	The DVB-T2 IRDs shall comply with the system software update defined in §10.11, Part A of this Specification, where applicable.
§10.12: User system software upgrade	The DVB-T2 IRDs shall be provided with alternative means for enabling system software upgrade.

Table 10: Exceptions for other DVB-T2 IRD implementations








¹⁴ AFD is used to present the video aspect ratio properly in response to the current AFD value.

¹⁵ MediaCorp had assigned logical channel numbering for their free-to-air DTV services. Equipment suppliers may need to customise the software to support §7.6 of IMDA TS DVB-T2 IRD.

Annex A

AFD Illustration for Required TV Output Display

The illustration below is the required outputs based on the AFD values specified in Table 3 of section 4.2.4.

INPUT				OUTPUT DISPLAY	
Source	Source Image	Broadcasted Frame	AFD Code	16:9	4:3
16:9		16:9	1000		
	1010				
4:3		4:3	1000		
		16:9	1001		

Annex B

Broadcast Channel Numbers and Centre Frequencies

	Bandwidth (MHz)	Channel Number	Centre Frequency (MHz)		Bandwidth (MHz)	Channel Number	Centre Frequency (MHz)
TV BAND III	7	5	177.5	TV BAND V	8	38	610
		6	184.5			39	618
		7	191.5			40	626
		8	198.5			41	634
		9	205.5			42	642
		10	212.5			43	650
		11	219.5			44	658
12	226.5	45	666				
TV BAND IV	8	21	474			46	674
		22	482			47	682
		23	490			48	690
		24	498			49	698
		25	506			50	706
		26	514			51	714
		27	522			52	722
		28	530			53	730
		29	538			54	738
		30	546			55	746
		31	554			56	754
		32	562	57	762		
		33	570	58	770		
		34	578	59	778		
		35	586	60	786		
		36	594	61	794		
		37	602	62	802		
		63	810				
		64	818				
		65	826				
		66	834				
		67	842				
		68	850				
		69	858				

Annex C

Classification Code Matrix

The EIT will carry DVB parental_rating_descriptor (with the tag of 0x55 as outlined in EN 300 468 [13]) alongside with the country code "SGP". The rating value (parental rating code) carried by this descriptor is associated with the matrix table shown below for on-screen display and channel block.

DVB parental rating codes for Singapore

Receiver End
← (Rating to Block) →

Parental Rating Code	SG Parental Code	SG Parental Classification	Description	OSD	User Setting Value						
					None	G	PG	PG13	NC16	M18	R21
					Green : Show Program			Red : Blocked until PIN is entered			
0x00	Undefined				Show	Show	Show	Show	Show	Show	Show
0x01	G	General	Suitable for all ages	G	Show	Blocked	Show	Show	Show	Show	Show
0x02											
0x03											
0x04	PG	Parental Guidance	Suitable for all, but parents should guide young	PG	Show	Blocked	Blocked	Show	Show	Show	Show
0x05											
0x06											
0x07											
0x08											
0x09											
0x0A	PG13	Parental Guidance 13	Suitable for persons aged 13 and above, parental guidance advised for children under 13.	PG13	Show	Blocked	Blocked	Blocked	Show	Show	Show
0x0B											
0x0C											
0x0D	NC16	No Children under 16	Suitable for persons aged 16 and above.	NC16	Show	Blocked	Blocked	Blocked	Blocked	Show	Show
0x0E											
0x0F	M18	Mature 18	Suitable for persons aged 18 and above.	M18	Show	Blocked	Blocked	Blocked	Blocked	Blocked	Show
0x10											
0x11											
0x12	R21	Restricted 21	Suitable for adults aged 21 and above	R21	Show	Blocked	Blocked	Blocked	Blocked	Blocked	Blocked

Broadcaster End
 ↑ (Hex Code of Transmitted Content)
 ↓

Where the broadcasted rating value is not classified (grey area), the DVB-T2 IRD shall interpret the rating to be the next higher classification. Example: If 0x05 is transmitted, it shall be treated as 0x0A (PG13). (By choosing a higher classification, it gives better protection in case the intent is to transmit a higher classification.)

Grey fill area are reserved for future use. (E.g. New classification/rating in future will be fitted into the grey area.)

Reference to the above Yellow Box:

The column "Parental Rating Code" (Hex code) is transmitted together with the television program. DVB-T2 IRD should be able to identify the assigned hex code according to the classification code.

Example: When user selects to block PG13, programs with classification Undefined, General (G) and Parental Guidance (PG) are allowed to display on screen while programs with classification PG13, NC16, M18 and R21 are blocked from viewing until the user entered the pin to unblock the program.

Annex D

Basic and Digital TV Function Keys

The DVB-T2 IRD's remote control shall include the following keys for basic TV functionality or equivalent:

- a) Power on/off [on/off] – turn the DVB-T2 IRD on and off
- b) Program up/down [P+, P-] – switch between programs
- c) Volume up/down [V+, V-] – adjust the volume output level
- d) Subtitle/option [Subt/option] – display the subtitle or select other user selectable options (e.g. change subtitling language if several available, audio language/track if several available, video aspect ratio output format etc.)
- e) Info [Info] – display additional information if available

The DVB-T2 IRD's remote control shall include the following keys for digital TV functions or equivalent:

- a) A navigation or pointing system for navigation on the OSD
- b) OK [OK] – a function that selects or confirms current choice or statement
- c) Multifunctional keys – four color-coded keys for non-dedicated functions. The colors shall be red, green, yellow and blue.
- d) Text [Text] – This function displays the Teletext as defined in this Specification.(Optional)
- e) Guide/EPG [Guide] – This function displays an Electronic Program Guide.

Annex E

DVB-T2 Performance Requirements

Identifier	SG1	SG2	SG3	SG4	SG5	SG6
Purpose	Fixed Outdoor Reception	Indoor Reception	Indoor Reception	Indoor Reception	Indoor Reception	Indoor Reception
Overall						
FFTSize	32K	16K	16K	16K	16K	16K
GI	1/32	1/16	1/16	1/16	1/16	1/16
SISO/MISO	SISO	SISO	SISO	SISO	SISO	SISO
PAPR	TR	TR	TR	TR	TR	TR
Bandwidth	8MHz	8MHz	8MHz	8MHz	8MHz	8MHz
Carrier Mode	Extended	Extended	Extended	Extended	Extended	Extended
Pilot Pattern	PP4	PP2	PP2	PP2	PP2	PP2
L1 Modulation	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK
Data Symbols per Frame (Ldata)	61	130	130	130	130	130
OFDM Symbols per Frame (Lf)	62	131	131	131	131	131
Frame Duration (ms)	229	250	250	250	250	250
Frames Per SuperFrame	2	2	2	2	2	2
PLP Parameter						
PLP Type	1	1	1	1	1	1
Time Interleaver Type (TIME_IL_Type)	0	0	0	0	0	0
Modulation	256 QAM	64QAM	64QAM	64QAM	256QAM	16QAM
Rate	2/3	3/5	2/3	3/4	3/5	2/3
FEC Type	Normal (64k)	Normal (64k)	Normal (64k)	Normal (64k)	Normal (64k)	Normal (64k)
Rotated QAM	No	No	No	No	No	No
FEC blocks per interleaving Frame Full channel (Trial mode)	200	151	151	151	202	101
TI blocks per frame (N_TI)	3	3	3	3	3	3
Frame Interval (I_JUMP)	1	1	1	1	1	1
Approx. Time Interleaving Length (ms)	78	84	84	84	84	82
Approx. Channel Data Rate (Mbit/s)	37.66	23.48	26.12	29.39	31.41	17.47
Performance assuming implementation losses is 2dB for PP2 and 1.5dB for PP4	8MHz UHF Band IV & V	8MHz UHF Band IV & V	8MHz UHF Band IV & V	8MHz UHF Band IV & V	8MHz UHF Band IV & V	8MHz UHF Band IV & V
C/N Performance on Gaussian channel (dB)	20.4	14.8	16.2	17.7	19.4	11.4
C/N performance on 0dB echo channel (dB)	24.6	18.0	19.7	22.0	23.1	14.3
Minimum receiver signal input levels on Gaussian channel (dBm)	-78.7	-84.3	-82.9	-81.4	-79.7	-87.7
Minimum IRD Signal Input Levels on 0dB echo channel (dBm)	-74.5	-81.1	-79.4	-77.1	-76.0	-84.8

Identifier	SG1	SG2	SG3	SG4	SG5	SG6
Purpose	Fixed Outdoor Reception	Indoor Reception	Indoor Reception	Indoor Reception	Indoor Reception	Indoor Reception
Receiver noise figure on Gaussian channel	6.0	6.0	6.0	6.0	6.0	6.0
Maximum Receiver Signal Input Levels (dBm)	-35	-35	-35	-35	-35	-35
Immunity to “digital” signals in Other Channels						
Digital ACI N+/-1 C/I (dB)	-28	-34	-32	-31	-28	-37
Digital ACI N+/-2 C/I (dB)	-38	-44	-42	-41	-38	-47
Digital ACI N+9 C/I (dB)	-28	-34	-32	-31	-28	-37
Immunity to Co-Channel Interference From Analogue TV Signals						
PAL B/G CCI C/I (dB)	5	-3	1	4	3	-6
Immunity to Adjacent Channel Interference From Analogue TV Signals						
PAL B/G ACI C/I N+/-1 (dB)	-33	-39	-37	-36	-33	-32
PAL B/G ACI C/I N+/-2 (dB)	-44	-50	-48	-47	-44	-53
PAL B/G ACI C/I N+9 (dB)	-44	-50	-48	-47	-44	-53
Performance in Time-Varying Channels 10Hz doppler (5Hz after AFC) 20us 0dB echo	3dB	3dB	3dB	3dB	3dB	3dB
Synchronisation for varying echo power levels in SFN (dB)	28.1	21.0	22.7	25.0	26.1	17.3
C/(N+I) Performance in Single Frequency Networks for more than one echo (dB)	24.6	18.0	19.7	22.0	23.1	14.3
C/(N+I) Performance in Single Frequency Networks inside the guard interval (dB)	24.6	18.0	19.7	22.0	23.1	14.3
C/(N+I) Performance in Single Frequency Networks outside the guard interval (dB)						
Delay us	Echo level dBc	Echo level dBc	Echo level dBc	Echo level dBc	Echo level dBc	Echo level dBc
-266	-12	-9	-10	-12	-13	-6
-230	-11	-8	-9	-11	-12	-5
-200	-10	-7	-8	-9	-11	-4
-150	-6	-3	-4	-6	-8	0
-120	-2	-2	-2	-2	-2	0
120	-2	-2	-2	-2	-2	0
150	-6	-3	-4	-6	-8	0
200	-10	-7	-8	-9	-11	-4
230	-11	-8	-9	-11	-12	-5
266	-12	-9	-10	-12	-13	-6

Note:

- 1) The performance requirement is based on 30 seconds error free video.
- 2) A copy of the test procedure is available upon request. Request can be sent to email account: DTV@imda.gov.sg.

[Note: The purpose of the Singapore DVB-T2 Test Suite is to facilitate compliance checks with this technical specification for Integrated Receiver Decoder (IRD) for use with the DVB-T2 system. It serves as a guideline for compliance testing for the defined transmission modes listed above and it is not exhaustive.]

Annex F**Proposed Logical Channel Numbering (LCN) Range**

MediaCorp's Free to Air (FTA) channel numbering on terrestrial platform

LCN	Channel
1	Preview Channel (Define as Reserved)
2	Channel 5
3	Channel 8
4	Suria
5	Vasantham
6	Channel News Asia
7	Channel U
8	Okto

Annex G

List of Broadcast Descriptors

Descriptors in use (exclude data broadcasting)	Tag	NIT	SDT	EIT	TOT	PMT
network_name_descriptor	0x40	*				
terrestrial_delivery_system_descriptor	0x5A	*				
T2_delivery_system_descriptor	0x7F/0x04 (ext)	*				
service_list_descriptor	0x48	*				
logical_channel_descriptor	0x83	*				
private_data_specifier_descriptor	0x5F	*				
service_descriptor	0x41		*			
multilingual_service_name_descriptor	0x5D		*			
component_descriptor	0x50			*		
short_event_descriptor	0x4D			*		
extended_event_descriptor	0x4E			*		
local_time_offset_descriptor	0x58				*	
iso_639_language_descriptor	0x0A					*
stream_identifier_descriptor	0x52					*
AC-3 descriptor	0x6A					*
subtitling_descriptor	0x59					*
teletext_descriptor	0x56					*
video_stream_descriptor	0x02					*
audio_stream_descriptor	0x03					*
content_descriptor	0x54			*		
parental_rating_descriptor	0x55			*		
Enhanced AC-3 descriptor	0x7A					*
AAC descriptor	0x7C					*

Descriptors required for SSU	Tag	NIT	SDT	EIT	TOT	PMT
linkage_descriptor	0x4A	*				
Data broadcast id descriptor	0x66					*

Note: The list is not exhaustive; it shows the typical descriptors that may be broadcast by terrestrial broadcasters.

Annex H

Addendum/Corrigendum

Changes to IMDA TS DVB-T2 IRD Issue 1, Dec 2016			
Page	TS Ref	Items Changed	Date of Issue
4	Part A § 2	Part A § 2 <u>References</u> Added references – [7a] IEC 61000-4-3 (2010-04): Testing and measurement techniques – Radiated, radio-frequency, electromagnetic field immunity test [9] ITU-T K.116 (2015): EMC requirements and test methods for radio telecommunication terminal equipment	DD Sep 2017
7	Part A § 4.2.1.2	Part A § 4.2.1.2 <u>EMS or immunity testing</u> This clause has been revised to provide clarity in the requirements and measurement techniques for radiated radio-frequency electromagnetic field immunity testing at the enclosure of the DVB- T2 IRD.	DD Sep 2017
33	Annex E	Annex E has been amended to include the DVB-T2 performance requirements for SG6 indoor reception mode. The SG6 transmission mode has been added to offer a more robust modulation scheme that will enhance the indoor reception.	DD Sep 2017

Changes to IDA/MDA TS DVB-T2 IRD Issue 1 Revision 2, May 2014			
Page	TS Ref	Items Changed	Date of Issue
2 & 28	- Part C	<u>Introduction</u> Part C <u>Exceptions for other DVB-T2 IRD implementations</u> Added a Part C to this Specification, which sets out the exceptions to the Part A requirements to which other DVB-T2 IRD implementations such as PC cards, dongles, portable TV or similar devices may not need to comply.	7 Dec 2016
3 & 32	Part A § 1.3 & Annex D	Part A § 1.3 <u>Scope of Part A: Basic DVB-T2 Requirements</u> Annex D <u>Basic and Digital Function Keys</u> Part A § 1.3 and Annex D have been amended to give clarity that the support for Teletext is “Optional”.	7 Dec 2016
6	Part A § 4	Part A § 4 <u>General Requirements</u> Part A § 4 has been revised to provide clarifications that regardless of power source (AC mains, external AC/DC converter, charger/power adapter or batteries) and equipment classification (fixed, vehicular or portable), DVB-T2 IRD shall be assessed for conformity to the relevant international standards for EMC and product safety.	7 Dec 2016

Changes to IDA/MDA TS DVB-T2 IRD Issue 1 Revision 2, May 2014 (Cont'd)			
Page	TS Ref	Items Changed	Date of Issue
19	Part A § 8.1.3	Part A § 8.1.3 <u>Support for hearing impaired</u> Amended Part A § 8.1.3 to give clarity that teletext descriptor will not be used to signal DVB subtitles as defined in Part A § 8.1.1.	7 Dec 2016
20	Part A § 8.2.3	Part A § 8.2.3 <u>Languages and Fonts</u> The following text has been added to give clarity on the multi-language support for EPG presentation. It is recommended to support the <code>multilingual_service_name_descriptor</code> . When <code>multilingual_service_name_descriptor</code> is present and the user preferred language for EPG presentation does not match any languages that are available, it is recommended to select the first service name appeared in said descriptor.	7 Dec 2016
21	Part A § 8.3	Part A § 8.3 <u>Multi-Language Support</u> The ISO 639 language codes have been amended to lower caps according to the broadcaster's transmission. A footnote has been included to indicate that DVB-T2 IRDs support of the ISO 639 language codes shall be case insensitive.	7 Dec 2016
22	Part A § 9.1 & 9.2	Part A § 9.1 <u>RF Input Connector</u> Part A § 9.2 <u>RF Output Connector</u> Part A § 9.1 and 9.2 have been amended to update the standard for RF connector.	7 Dec 2016
23	Part A § 9.11	Part A § 9.11 has been amended to give clarity on the limitations in storage and extraction of recordings should the DVB-T2 IRD is capable of recording broadcast services in persistent memory.	7 Dec 2016
24	Part A § 10.6.1	Part A § 10.6.1 <u>Addition of multiplex on a network</u> Part A § 10.6.1 has been amended to give clarity on the receiver behavior during addition of multiplex on a network.	7 Dec 2016
25	Part A § 10.11	Part A § 10.11 <u>System software update (SSU/OTA/OAD)</u> A footnote has been included to indicate that for DVB-T2 IRD modules, STBs and IDTVs designed for commercial use (e.g. Hotel TV system), manufacturers may provide other means of performing software upgrade.	7 Dec 2016

Changes to IDA/MDA TS DVB-T2 IRD Issue 1 Revision 1, Mar 2013			
Page	TS Ref	Items Changed	Date of Issue
3 & 18 & 19	Part A § 1.3 & § 7.4 & § 8.7	Part A § 1.3 <u>Scope of Part A: Basic DVB-T2 Requirements</u> Part A § 7.4 <u>Teletext</u> Part A § 8.7 <u>Additional Requirements for Composite Video Interface</u> The requirement to support Teletext service has been amended as "Optional".	5 May 2014
8	Part A § 4.3.5	<u>Lip Sync</u> Lip sync requirement has been amended as "Recommended". Manufacturers should ensure this basic performance of their product.	5 May 2014
8 25	Part A § 4.3.3 Part B § 5	<u>Decoding & Presentation Options for 2 Channels of Decoder Output</u> <u>Decoding & Presentation Options for Multi-Channel Decoder</u> The support for HE-AAC bit stream pass through via S/PDIF and HDMI output has been amended as "Optional". For multi-channel receiver, there is no impact to the consumer as HE-AAC 5.1 can be trans-coded to AC-3 or DTS for decoding by existing AV Receiver.	5 May 2014
8 & 19 25	Part A § 4.3.3 & § 8.9 Part B § 5	Digital Audio Data Stream Output (S/PDIF) HDMI Audio Return Channel (ARC) output has been included in Part A § 4.3.3 and § 8.9 and Part B § 5 to give clarity that the requirement for S/PIF also applies to the HDMI ARC interface.	5 May 2014
9	Part A § 4.3.8	Added Part A § 4.3.8 to give clarity on the audio prioritizing, according to the broadcaster's transmission.	5 May 2014
14	Part A § 6.6.2	Logical Channel Descriptor (Version 2) The following text has been added to give clarity on the expected behaviour of the IRD if it does not offer any User Interface (UI) to select the Channel List described in LCNV2. When several Channel Lists are available from same network (original network id) and same country code for the IRD during first time installation (or complete re-installation), the receiver shall choose the channel list as the default one with following priority: The IRD shall choose the one with lowest list_id value OR let the viewer choose from a list, (typically using the channel_list_name)	5 May 2014

Changes to IDA/MDA TS DVB-T2 IRD Issue 1 Revision 1, Mar 2013 (Cont'd)			
Page	TS Ref	Items Changed	Date of Issue
17	Part A § 7.2.3	<p><u>Languages and Fonts</u></p> <p>The following text is added to give clarity on the multi-language support for EPG presentation:</p> <p>The DVB-T2 IRD shall support EPG presentation signalled with ENG, ZHO and MSA by offering a means to select the EPG language.</p> <p>It is optional to support EPG presentation signalled with TAM.</p> <p>When EPG data is offered in multiple languages, it is recommended that the DVB-T2 IRD provides an easy to use option to allow the user to select the language for EPG presentation.</p> <p>When the user preferred language for EPG presentation does not match any languages that are available, it is recommended to select the language of the First EPG data (Short Event Descriptor) appeared in the descriptor loop of the of the Event Information Table (EIT).</p> <p>It is recommended to allow the user to toggle the languages when viewing the EPG presentation.</p>	5 May 2014
18	Part A § 7.3	<p><u>Multi-Language Support (For Audio)</u></p> <p>The ISO 639 language codes “QAB” and “QAC” have been included to give broadcasters the flexibility in adopting the appropriate signalling for the Second and the Third Audio, respectively.</p>	
21	Part A § 9.6.2	<p>Addition or removal of service on a multiplex</p> <p>The description on EIT- present/following (p/f) was removed as the processing of EIT p/f is not required for addition of a service. In addition, the description on the SDT (actual) to be transmitted at least every 2 sec was also removed as it is a transmission requirement.</p>	5 May 2014
22	Part A § 9.10	<p>Channel Zapping Time</p> <p>The channel zapping time between channels within same multiplex has been amended to be between 1.5 and 3 seconds to give manufacturers the flexibility in deployment of the video decoder chipsets.</p>	5 May 2014

Changes to IDA/MDA TS DVB-T2 IRD Issue 1 Revision 1, Mar 2013 (Cont'd)			
Page	TS Ref	Items Changed	Date of Issue
25	Part B § 6	<p><u>Audio Description (AD)</u></p> <p>The requirement to support audio description in receiver-mix mode for multi-channel receiver has been amended as “Optional” in view that there is no immediate plan to implement audio description in receiver-mix mode. Nevertheless, AD in Broadcast-mix mode is supported by both stereo and multi-channel receivers.</p> <p>The following text is included to give clarity on the method for transporting of the audio description between HE-AAC and DD+:</p> <p>The audio description service shall be provided as an associated service in a separate stream encoded with the same audio codec as used for the main program.</p> <p>In case of the use of E-AC3 as audio codec, the mixing data shall be included as part of the E-AC3 bit stream as defined in ETSI TS 102 366 Annex E [39] and the AD_descriptor defined in ETSI TS 101 154 Annex E.2 [1], if present, shall be ignored.</p>	5 May 2014
27	Annex C	<p><u>Classification Code Matrix</u></p> <p>Annex C has been amended to indicate that “Where the broadcasted rating value is not classified (grey area), the DVB-T2 IRD shall interpret the rating to be the next higher classification. Example: If 0x05 is transmitted, it shall be treated as 0x0A (PG13).”</p>	5 May 2014

Changes to IDA/MDA TS DVB-T2 IRD Issue 1, Nov 2012							
Page	TS Ref	Items Changed	Date of Issue				
22	Part A § 10 [1]	<p><u>Scope of Part A: Basic DVB-T2 Requirements</u></p> <p>Existing reference to the ETSI TS 101 154 v1.10.1 (2011-06) has been updated with the latest version v.1.11.1 (2012-11) for use of video and audio coding in broadcasting applications based on the MPEG-2 transport stream. This latest version provides clarity to the metadata used in the multi-channel audio.</p> <p>As revisions to the ETSI TS 101 154 have been developed largely in a backward compatible manner, updating of this reference will not bring about any change to the mandatory requirements previously defined for the DVB-T2 IRD.</p>	15 Mar 2013				
3	Part A § 1.1 e)	"E-AC3" has been deleted from the existing text as E-AC3 is an additional requirement for supporting multi-channel audio under Part B of the Specification.					
6	Part A § 4.2.1	<p><u>Video Decoding</u></p> <p>"§ 5.2" of ETSI TS 101 154 for supporting the 25 Hz MPEG2 HDTV video format has been deleted from the existing text to align with Table 1, which only requires that the 25 Hz MPEG2 SDTV video format be supported.</p>	15 Mar 2013				
10	Part A § 5.3.2	<p><u>Operating Modes</u></p> <p>As Part A § 5 has specified that the frontend/tuner shall comply with the Layer 1 signalling requirements of the DVB-T2 baseline system defined in the ETSI 302 755 v1.3.1, signalling formats for Peak Average Power Ratio (PAPR) reduction given in Table 6 are replaced as shown below, and support for scrambling of L1 post signalling is indicated as required.</p> <table border="1" data-bbox="408 1301 1233 1608"> <tr> <td>Signalling format for Peak Average Power Ratio (PAPR) reduction</td> <td>L1-ACE is used and TR is used on P2 symbols only; L1-ACE and ACE only are used; L1-ACE and TR only are used; or L1-ACE, ACE and TR are used.</td> </tr> <tr> <td>Scrambling of L1 post signalling (L1_POST_SCRAMBLED)</td> <td>Feature shall be supported by the DVB-T2 IRD.</td> </tr> </table> <p>Also, the support for time frequency slicing (TFS) is not required for the DVB-T2 IRD with single front-end/tuner.</p>	Signalling format for Peak Average Power Ratio (PAPR) reduction	L1-ACE is used and TR is used on P2 symbols only; L1-ACE and ACE only are used; L1-ACE and TR only are used; or L1-ACE, ACE and TR are used.	Scrambling of L1 post signalling (L1_POST_SCRAMBLED)	Feature shall be supported by the DVB-T2 IRD.	15 Mar 2013
Signalling format for Peak Average Power Ratio (PAPR) reduction	L1-ACE is used and TR is used on P2 symbols only; L1-ACE and ACE only are used; L1-ACE and TR only are used; or L1-ACE, ACE and TR are used.						
Scrambling of L1 post signalling (L1_POST_SCRAMBLED)	Feature shall be supported by the DVB-T2 IRD.						

Changes to IDA/MDA TS DVB-T2 IRD Issue 1, Nov 2012 (Cont'd)			
Page	TS Ref	Items Changed	Date of Issue
12	Part A § 6.6	<p><u>Service Identification and Logical Channel Number (LCN)</u></p> <p>The “Original Network ID value (ONID)” has been added to the list of DVB identification values that has been uniquely assigned for and used by the broadcaster in Singapore. This provides further information of the network identification values that have been allocated to Singapore for broadcasting applications.</p>	15 Mar 2013
18	Part A § 8.9	<p><u>Digital Audio Data Stream Output (Optional)</u></p> <p>For clarity of reference, the text “section 4” has been replaced by “§ 4.3.3 of Part A and § 5 of Part B”.</p>	15 Mar 2013
21	Part A § 9.11	<p><u>System Software Update</u></p> <p>References to “ISO/IEC 13818-1 [5], ETSI TS 101 154 [1]” have been deleted as reference to “ETSI TS 102 006 [21]” should suffice for specifying requirements for system software update in DVB systems.</p>	15 Mar 2013