

Telecommunications Standards Advisory Committee (TSAC)

Technical Specification

Land Mobile Radio Equipment

IDA TS LMR Issue 1 Rev 5, June 2014

Infocomm Development Authority of Singapore Resource Management & Standards 10 Pasir Panjang Road #10-01 Mapletree Business City Singapore 117438

© Copyright of IDA, 2014

This document may be downloaded from the IDA website at http://www.ida.gov.sg and shall not be distributed without written permission from IDA

Telecommunications Standards Advisory Committee (TSAC)

The TSAC advises IDA on the setting of ICT standards as well as on the development and recommendation of specifications, standards, information notes, guidelines and other forms of documentation for adoption and advancement of the standardisation effort of the Singapore ICT industry (hereafter termed "IDA Standards").

Telecommunications standards-setting in Singapore is achieved with the assistance of TSAC, where professional, trade and consumer interest in telecommunications standards is represented on the TSAC with representatives from network and service operators, equipment suppliers and manufacturers, academia and researchers, professional bodies and other government agencies.

List of TSAC Members

TSAC Chairman:

Mr Raymond Lee	Director (Resource Management & Standards)
	Infocomm Development Authority of Singapore

TSAC Members:

Mr Lim Yuk Min	Senior Executive Consultant (Resource Management
(TSAC Vice-Chairman)	and Standards)
	Infocomm Development Authority of Singapore
Dr Lee Shiang Long	Executive Director
Di Lee Onlang Long	Institute for Infocomm Research (I2R)
Mr Darwin Ho Kang Ming	Member
	Association of Telecommunications Industry of
	Singapore
Mr Yip Yew Seng	Honorary Secretary
	Association of Telecommunications Industry of
	Singapore
Mr Goh Kim Soon	SVP (Technology Support / Technology Support, IMD)
	Mediacorp Pte Ltd
Mr Lim Chin Siang	Director (Technology)
5	Media Development Authority
Ms Tan Sze Siang	Deputy Director (Digital Broadcasting Deployment
C C	Office)
	Media Development Authority
Mr Patrick Scodeller	Chief Technical Officer
	M1 Limited
Mr Lee Wing Kai	General Manager
	Engineering Radio Planning
	M1 Limited
Assoc Prof Li Kwok Hung	Nanyang Technological University
	School of Electrical & Electronic Engineering
Assoc Prof Xiao Gaoxi	Nanyang Technological University
	School of Electrical & Electronic Engineering
Assoc Prof Hari Krishna	National University of Singapore
Garg	Department of Electrical & Computer Engineering
Prof Ko Chi Chung	National University of Singapore
	Department of Electrical & Computer Engineering
Assoc Prof Tham Chen	National University of Singapore

Khong	Department of Electrical & Computer Engineering
Mr Chong Siew Loong	Vice President (Network and Systems)
	Nucleus Connect Pte Ltd
Mr Tiong Onn Seng	Director – Project & Operations
	Opennet Pte Ltd
Mr Daniel Teo	Director – Technical Services
	Opennet Pte Ltd
Mr Aw Peng Soon	Chairman of SiTF Wireless Chapter
, C	VP, ANTLabs
	Singapore Infocomm Technology Federation
Mr Edmund Quek	Associate Director (Radio Network Performance)
	Singapore Telecommunications Ltd
Mr Lim Yong Nam	Director (Voice Engineering, Next Gen IP Networks)
	Singapore Telecommunications Ltd
Mr Lee Yeu Ching	Director (Outside Plant Engineering)
	Singapore Telecommunications Ltd
Mr Soh Keng Hock	Director (Private IP Engineering)
	Singapore Telecommunications Ltd
Dr Wong Woon Kwong	Director of the Office of Research and Industry
	Collaborations
	Singapore University of Technology and Design
Mr Tay Wei Kiang	Assistant Vice President
	Business Solutions & Fixed Services
	StarHub Integrated Network Engineering
	StarHub Ltd
Mr Liong Hang Chew	Assistant Vice President
	Personal Solutions & Integrated Applications
	StarHub Integrated Network Engineering
	StarHub Ltd
Ms Woo Yim Leng	Senior Manager
	Infocomm Development Authority of Singapore

Contents

Section		Page
1	General Requirements	3
1.1 1.2 1.3	Scope of Specification Design of LMR Equipment Safety and Health	3 3 3
2	Technical Requirements	3
3	Compliance with Technical Requirements	3
Table 1	Technical Requirements for Radio Equipment to be used in Land Mobile Radio Services	6
Annex A	Continuous Tone Code Sub-audible Squelch (CTCSS) Code Frequency	11
Annex B	Addendum/Corrigendum Changes to IDA TS LMR, Issue 1 Rev 3, May 11 Changes to IDA TS LMR, Issue 1 Rev 2, Feb 11 Changes to IDA TS LMR, Issue 1 Rev 1, Aug 06 Changes to IDA TS LMR, Issue 1, Jul 05 Changes to IDA TS 101, 102, 107, 108, 111, 112, 115 and TETRA	12

NOTICE This Specification is subject to review and revision.

NOTICE

THE INFOCOMM DEVELOPMENT AUTHORITY OF SINGAPORE ("IDA") MAKES NO WARRANTY OF ANY KIND WITH REGARD TO THE MATERIAL PROVIDED HEREIN AND EXCLUDES ANY EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS OF NON-INFRINGEMENT, MERCHANTABILITY, SATISFACTORY QUALITY AND FITNESS FOR A PARTICULAR PURPOSE. SUBJECT TO THE MAXIMUM EXTENT PERMITTED UNDER LAW, IDA SHALL NOT BE LIABLE FOR ANY ERRORS AND/OR OMISSIONS CONTAINED HEREIN OR FOR ANY LOSSES OR DAMAGES (INCLUDING ANY LOSS OF PROFITS, BUSINESS, GOODWILL OR REPUTATION, AND/OR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES) IN CONNECTION WITH THE USE OF THIS MATERIAL.

IDA DRAWS ATTENTION TO THE POSSIBILITY THAT THE PRACTICE OR IMPLEMENTATION OF THIS STANDARD MAY INVOLVE THE USE OF INTELLECTUAL PROPERTY RIGHTS AND TAKES NO POSITION CONCERNING THE EXISTENCE, VALIDITY AND/OR APPLICABILITY OF ANY SUCH INTELLECTUAL PROPERTY RIGHTS, WHETHER ASSERTED BY TSAC MEMBERS OR ANY THIRD PARTY.

AS OF THE DATE OF APPROVAL OF THIS STANDARD, IDA HAS NOT RECEIVED WRITTEN NOTICE OF ANY PATENT RIGHTS WHICH MAY BE RELEVANT IN RELATION TO THE IMPLEMENTATION OF THIS STANDARD. HOWEVER, IMPLEMENTERS ARE CAUTIONED THAT THIS MAY NOT REPRESENT THE LATEST INFORMATION AND ARE THEREFORE STRONGLY URGED TO CHECK WITH THE RELEVANT DATABASE IN ITU, ISO, IEC OR THE RELATED STANDARDS DEVELOPMENT ORGANISATION FOR INFORMATION OF PATENT RIGHTS. IMPLEMENTERS ARE ADVISED TO OBTAIN THEIR OWN LEGAL AND/OR TECHNICAL ADVICE IN RELATION TO THE IMPLEMENTATION OF THE STANDARD IF REQUIRED.

1. General Requirements

1.1 Scope of Specification

- 1.1.1 This Specification defines the minimum technical requirements for radio equipment to be used in Land Mobile Radio (LMR) services. LMR equipment shall operate in one of the authorised frequency bands or frequencies, and transmit within the corresponding output power levels given in Table 1.
- 1.1.2 LMR equipment may be base stations used in fixed locations, mobile stations used in vehicles or as transportable stations, or handheld portable stations that come with an external antenna or an integral antenna. Applications may include speech and/or data communication, and may be using digital radio technologies such as the Integrated Digital Enhanced Network (iDEN), Terrestrial Trunked Radio (TETRA), Digital Mobile Radio (DMR) or NXDN technology (see Table 1).

1.2 Design of LMR Equipment

LMR Equipment shall be designed to meet the following basic objectives:

- (a) The equipment shall not be constructed with any external or readily accessible control which permits the adjustment of its operation in a manner that is inconsistent with this Specification.
- (b) The device shall be marked with the supplier/manufacturer's name or identification mark, and the supplier/manufacturer's model or type reference. The markings shall be legible, indelible and readily visible.

1.3 Safety and Health

- 1.3.1 Where appropriate, the LMR equipment shall comply with the International Commission on Non-Ionising Radiation Protection (ICNIRP) guidelines for limiting exposure to time-varying EMFs in the frequency range up to 300 GHz.
- 1.3.2 It should be noted that compliance with any radiation safety standard does not by itself confer immunity from legal obligations and requirements imposed by national health or safety authorities.

2 Technical Requirements

The LMR Equipment shall comply with the RF output power and spurious emissions given in Table 1, operating in its intended frequency band or frequencies. It shall fulfil the relevant requirements of this Specification on all the permitted frequencies which it is intended to operate.

3 Compliance with Technical Requirements

3.1 Suppliers shall demonstrate that the LMR equipment has been tested and certified for conformity with the applicable technical requirements stipulated in Table 1 of this Specification. Measurement methods and conditions shall be with reference to one of the following standards, whichever is applicable for the equipment under test (refer to Table 1 for guidance):

- ETSI EN 300 086-1 Electromagnetic compatibility and Radio spectrum Matters (ERM); Land Mobile Service; Radio equipment with an internal or external RF connector intended primarily for analogue speech; Part 1: Technical characteristics and methods of measurement
- ETSI EN 300 296-1 Electromagnetic compatibility and Radio spectrum Matters (ERM); Land Mobile Service; Radio equipment using integral antennas intended primarily for analogue speech; Part 1: Technical characteristics and methods of measurement
- FCC Part 90 Federal Communications Commission, Part 90 Private Land Mobile Radio Services
- ETSI EN 300 113-1 Electromagnetic compatibility and Radio spectrum Matters (ERM); Land Mobile Service; Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector; Part 1: Technical characteristics and methods of measurement
- ETSI EN 301 166-1
 Electromagnetic compatibility and Radio spectrum Matters (ERM); Land Mobile Service; Radio equipment for analogue and/or digital communication (speech and/or data) and operating on narrow band channels and having an antenna connector; Part 1: Technical characteristics and methods of measurement
- ETSI EN 300 390-1 Electromagnetic compatibility and Radio spectrum Matters (ERM); Land Mobile Service; Radio equipment intended for the transmission of data (and/or speech) and using an integral antenna; Part 1: Technical characteristics and methods of measurement
- ETSI EN 300 394-1 Terrestrial Trunked Radio (TETRA); Conformance Testing Specification; Part 1: Radio
- ETSI EN 300 396-2 Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 2: Radio aspects
- ETSI EN 300 392-2 Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)
- ETSI EN 303 035-1 Terrestrial Trunked Radio (TETRA); Harmonised EN for TETRA equipment covering essential requirements under article 3.2 of the R&TTE Directive; Part 1: Voice plus Data (V+D)
- ETSI EN 303 035-2 Terrestrial Trunked Radio (TETRA); Harmonised EN for TETRA equipment covering essential requirements under article 3.2 of the R&TTE Directive; Part 2: Direct Mode Operation (DMO)

- ETSI TS 102 361-1
 Electromagnetic compatibility and Radio spectrum Matters (ERM);Digital Mobile Radio (DMR) Systems; Part 1: DMR Air Interface (AI) protocol
- ETSI TS 102 361-2
 Electromagnetic compatibility and Radio spectrum Matters (ERM);Digital Mobile Radio (DMR) Systems; Part 2: DMR voice and generic services and facilities
- ETSI TS 102 361-3 Electromagnetic compatibility and Radio spectrum Matters (ERM);Digital Mobile Radio (DMR) Systems; Part 3: DMR data protocol
- ETSI TS 102 361-4 Electromagnetic compatibility and Radio spectrum Matters (ERM);Digital Mobile Radio (DMR) Systems; Part 4: DMR trunking protocol
- 3.2 Where appropriate, suppliers shall demonstrate the LMR equipment has been tested according to measurement methods and limits for:
 - (a) EMC emissions from the DC power or AC mains power input/output ports defined in ETSI EN 301 489-1 or IEC CISPR 22; and
 - (b) Electrical safety defined in the IEC 60950-1

Table 1: Technical Requirements for Radio Equipment to be used in Land Mobile Radio Services

Item No.	Operating Frequencies	Channel Spacing	Max RF Power Output	Spurious Emissions	Test Reference	Applications	Additional Requirements			
1	80 MHz				ETSI EN 300 086-1 for radio equipment with an internal or	Base, mobile	 Suppliers registering equipment 			
	150 MHz	12.5 kHz	Base/Mobile: 25 W ERP Note 1	< 20 nW	external RF connector; ETSI EN 300 296-1 for radio	or portable equipment for	for use in Private Radio Network operation are required to first seek			
	450 MHz		Portable: 5 W ERP ^{Note 1}	. 20	equipment with integral antenna; or FCC Part 90 for Private Land	analogue	the approval of IDA on the frequencies to be used.			
	900 MHz	25 kHz			Mobile Radio Services		 Suppliers registering equipment 			
2	Mobile Tx:						for use in Public Radio Data Communication Networks are advised to check with Network			
	415 – 417 MHz	12.5 kHz/			FTSLEN 300 113-1 for radio	Operations on the exact operating frequencies used.				
	Base Tx:	25 kHz	Base: 25 W	W43 + 10log(P) where P = Rated carrier power in Wattsequipment with antenna connector; ETSI EN 300 390-1 for radio equipment with integral antenna; or FCC Part 90 for Private Land Mobile Radio ServicesBase, mobile or portable equipment for data- Operation unc requires IDA is or portable equipment with antegral antenna; or data		ETSI EN 300 113-1 for radio		 Operation under this provision 		
	425 – 427 MHz		Mobile: 25 W where P = equipment with antenna connector, ETSI EN 300 390-1 for radio base, model ERP Note 1 Rated carrier power in ETSI EN 300 390-1 for radio or portable Portable: 5 W power in ECC Part 90 for Private Land data		5 W Rated carrier	NP Nobile: 25 W where P =			or portable	requires IDA licensing.
	Mobile Tx:					FCC Part 90 for Private Land	equipment for	 Provision does not apply to equipment with special function 		
	806 – 818 MHz	25 kHz	ERP Note 1		Mobile Radio Services		such as tone coded squelch, selective calling decoders or			
	Base Tx:							encoders, which shall be disabled during testing.		
	851 – 863 MHz									

^{Note 1} Effective Radiated Power (ERP) refers to radiation of a half wave tuned dipole, which is used for frequencies below 1 GHz.

Table 1: Technical Requirements for Radio Equipment to be used in Land Mobile Radio Services (Continued)

Item No.	Operating Frequencies	Channel Spacing	Max RF Power Output	Spurious Emissions	Test Reference	Applications	Additional Requirements
3	446.3250 – 446.4750 MHz	12.5 kHz	1 W ERP ^{Note 1}	< 2 nW	ETSI EN 300 296-1 for radio equipment with integral antenna	Multi-channel portable radio equipment for analogue speech (localised use)	 Operation above 500 mW ERP under this provision requires IDA licensing. Frequencies specified in this provision are to be used on non-interference, non-protected and shared basis. Provision does not apply to equipment with special function such as tone coded squelch, selective calling decoders or encoders, which shall be disabled during testing. Repeaters and amplifiers are not allowed to be used with the multi-channel portable radio equipment to extend the range of coverage. Equipment shall use integral antenna only, and be designed to ensure that no antenna other than that furnished by the responsible party shall be used. Equipment shall be equipped with the Continuous Tone Code Sub-audible Squelch (CTCSS) capability with a minimum number of 10 distinct tones out of 32 as specified in Annex A of this Specification.

Note 1 Effective Radiated Power (ERP) refers to radiation of a half wave tuned dipole, which is used for frequencies below 1 GHz.

Table 1: Technical Requirements for Radio Equipment to be used in Land Mobile Radio Services (Continued)

Item No.	Operating Frequencies	Channel Spacing	RF Power Output	Spurious Emissions	Test Reference	Applications	Additional Requirements
4	446.00 – 446.10 MHz	12.5 kHz	500 mW ERP	< 2 nW	ETSI EN 300 296-1 for radio equipment with integral antenna	Portable radio equipment for analogue speech (localised use)	 Frequencies specified in this provision are to be used on non-interference, non-protected and shared basis. Provision does not apply to equipment with special function such as tone coded squelch, selective calling decoders or encoders, which shall be disabled during testing. Repeaters and amplifiers are not allowed to be used with the multi-channel portable radio equipment to extend the range of coverage. Equipment shall use integral antenna only, and be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Note 1 Effective Radiated Power (ERP) refers to radiation of a half wave tuned dipole, which is used for frequencies below 1 GHz.

Table 1: Technical Requirements for Radio Equipment for use in Land Mobile Radio Services (Continued)

Item No.	Operating Frequencies	Channel Spacing	Max RF Power Output	Spurious Emissions	Test Reference	Applications	Additional Requirements
5	Tx: 806 – 825 MHz Rx: 851 – 870 MHz	25 kHz	Base/Mobile: 25 W ERP ^{Note 1} Portable: 5 W ERP ^{Note 1}	43 + 10log(P) where P = Rated carrier power in Watts	FCC Part 90 for Private Land Mobile Radio Services	Base, mobile and portable equipment for digital radio mobile system such as iDEN trunked mobile radio system	 Operation under this provision requires IDA licensing. If the radio equipment supports connection to the public mobile radio network, suppliers shall demonstrate that equipment has been tested and certified to comply with the relevant requirements given in IDA TS CMT. If the radio equipment supports WLAN mode, suppliers shall demonstrate that equipment has been tested and certified to comply with the relevant requirements for WLAN given in the IDA TS SRD.
6	380 – 400 MHz	25 kHz	25 W ERP ^{Note 1}	-36 dBm in 100 kHz bandwidth in frequency range 9 kHz to 1 GHz -30 dBm in 1 MHz bandwidth in frequency range 1 to 4 GHz	Conformity assessment requirements: ETSI EN 300 394-1, EN 300 396-2 and EN 300 392-2 Testing Requirements: ETSI EN 303 035-1 and EN 303 035-2.	Base and mobile stations for digital radio mobile system such as TETRA trunked mobile radio system	 Operation under this provision requires IDA licensing.

Note 1 Effective Radiated Power (ERP) refers to radiation of a half wave tuned dipole, which is used for frequencies below 1 GHz.

Table 1: Technical Requirements for Radio Equipment for use in Land Mobile Radio Services (Continued)

ltem No.	Operating Frequencies	Channel Spacing	Max RF Power Output	Spurious Emissions	Test Reference	Applications	Additional Requirements
7	136 – 174 MHz 400 – 410 MHz 430 – 450 MHz	6.25 kHz or equivalent/ 12.5 kHz	Base/Mobile: 25 W ERP Note 1 Portable: 5 W ERP Note 1	43 + 10log(P) where P = Rated carrier power in Watts	ETSI EN 300 113-1 for radio equipment with antenna connector; ETSI EN 301-166-1 for radio equipment operating at narrowband channel with antenna connector; ETSI EN 300 390-1 for radio equipment with integral antenna; or FCC Part 90 for Private Land Mobile Radio Services	Base, mobile and portable equipment for digital conventional or trunked mobile radio system such as DMR, NXDN or equivalent	 Operation under this provision requires IDA licensing. If the radio equipment supports connection to the public mobile radio network, suppliers shall demonstrate that equipment has been tested and certified to comply with the relevant requirements given in IDA TS CMT. If the radio equipment supports WLAN mode, suppliers shall demonstrate that equipment has been tested and certified to comply with the relevant requirements for WLAN given in the IDA TS SRD.

^{Note 1} Effective Radiated Power (ERP) refers to radiation of a half wave tuned dipole, which is used for frequencies below 1 GHz.

Annex A: Continuous Tone Code Sub-audible Squelch (CTCSS) Code Frequency

67.0	110.9	146.2	192.8
71.9	114.8	151.4	203.5
77.0	118.8	156.7	210.7
82.5	123.0	162.2	218.1
88.5	127.3	167.9	225.7
94.8	131.8	173.8	233.6
103.5	136.5	179.9	241.8
107.2	141.	186.2	250.3

The standard frequencies (in Hz) available for assignment are shown below.

Annex B: Corrigendum / Addendum

	Changes to IDA TS LMR, Issue 1, Rev 4, June 11						
Page	TS Ref.	Items Changed	Effective Date				
7	Table 1 (3)	The use of the frequency band 477 – 477.25 MHz has been migrated to the frequency band 446.3250 – 446.4750 MHz with the maximum RF Power output increased to 1 W ERP.	23 June 14				

	Changes to IDA TS LMR, Issue 1, Rev 3, May 11						
Page	TS Ref.	Items Changed	Effective Date				
9, 10	Table 1 (5, 7)	Editorial changes to the column, 'Additional Requirements' – Reference to IDA TS GSM-MT was changed to IDA TS CMT	17 June 11				

Changes to IDA TS LMR, Issue 1, Rev 2, Feb 11			
Page	TS Ref.	Items Changed	Effective Date
		Change of IDA's address at cover page to Mapletree Business City.	1 May 11

Changes to IDA TS LMR, Issue 1, Rev 1, Aug 06			
Page	TS Ref.	Items Changed	Effective Date
10	Table 1(7)	Provision of services operating with 6.25 kHz channel spacing is intended for improving the spectrum efficiency of equipment operating in the following frequency bands:	Feb 11
		a. 136.00 – 174.00 MHz b. 400.00 – 410.00 MHz c. 430.00 – 450.00 MHz	

Changes to IDA TS LMR, Issue 1, Jul 05			
Page	TS Ref.	Items Changed	Effective Date
6 and 7	Table 1(3) and 1(4)	Provisions have been aligned with the Schedule to the Telecommunications (Exemption from sections 33, 34(1)(b) and 35) (Amendment) Notification 2006:	Jun 06
		d. 477.00 – 477.25 MHz frequency band, output power up to 500 mW ERP	

Changes to IDA TS LMR, Issue 1, Jul 05			
Page	TS Ref.	Items Changed	Effective Date
		e. 446.00 – 446.10 MHz frequency band, output power up to 500 mW ERP	

	Changes to IDA TS 101, 102, 107, 108, 111, 112, 115 and TETRA			
Page	TS Ref.	Items Changed	Effective Date	
-	_	 This Specification supersedes the following IDA Type Approval Specifications: a. IDA TS 101 Issue 1 Rev 4 b. IDA TS 102 Issue 1 Rev 4 c. IDA TS 107 Issue 1 Rev 3 d. IDA TS 108 Issue 1 Rev 3 e. IDA TS 111 Issue 1 Rev 3 f. IDA TS 112 Issue 1 Rev 3 g. IDA TS 115 Issue 1 h. IDA TS TETRA Issue 1 Rev 1 	21 Jul 05	
-	_	Title of Specification has been renamed as "Technical Specification for Land Mobile Radio Equipment" (IDA TS LMR Issue 1). Changes are mainly editorial in nature. The essential technical requirements for conformity assessment remain unchanged.	21 Jul 05	